TM 11-5820-335-35P

DEPARTMENT OF THE ARMY TECHNICAL MANUAL

D-17

DS, GS AND DEPOT MAINTENANCE
REPAIR PARTS AND SPECIAL TOOL LISTS

TRANSMITTER, RADIO T-195/GRC-19, T-195A/GRC-19, T-195B/GRC-19



HEADQUARTERS, DEPARTMENT OF THE ARMY

30 DECEMBER 1965

TECHNICAL MANUAL
No. 11–5820–335–35P

HEADQUARTERS
DEPARTMENT OF THE ARMY
WASHINGTON, D. C. 20315, *30 December 1965*

TRANSMITTER, RADIO T–195/GRC–19, T–195A/GRC–19, T–195B/GRC–19

		Paragraph	Page
SECTION I.	INTRODUCTION		
	Scope	1	ii
	Parts for maintenance	2	iii
	Additional Repair Parts, authorization	3	iii
	Electron tubes	4	iii
	Requisitioning information	5	iii
	References	6	iii
	Reporting of equipment manual improvements	7	iii
SECTION II.	FUNCTIONAL PARTS LIST		
	Transmitter, Radio T–195/GRC–19, T–195A/GRC–19, T–195B/GRC–19		1
Group I.	Transmitter, Radio T–195/GRC–19, T–195A/GRC–19, T–195B/GRC–19		1
II.	Amplifier, Electronic Control		1
III.	Amplifier, Radio Frequency		6
IV.	Control, Antenna Tuning		21
V.	Dynamotor, High Voltage		26
VI.	Dynamotor, Low Voltage		26
VII.	Modulator Subassembly		27
VIII.	Oscillator, Radio Frequency Exciter Assembly		34
IX.	Oscillator, Radio Frequency (VFO)		42
X.	Panel and Frame Assembly		43
XI.	Power Supply, High Voltage Transistorized		61
XII.	Power Supply, High Voltage Transistorized		62
XIII.	Power Supply, Low Voltage Transistorized		64
XIV.	Transmitter, Discriminator Subassembly		67
XV.	Tuner, R.F. Inductor Subassembly		69
XVI.	Power Supply, Transistorized, High Voltage		72
XVII.	Power Supply, Transistorized, Low Voltage		73

*This manual supersedes TM 11–5820–335–35P, dated 21 December 1961, including C3, 4 April 1963, and C5, 1 December 1964.

SECTION I

INTRODUCTION

1. Scope

a. This manual lists the quantities of repair parts for direct support, general support, and depot maintenance and is a basis for requisitioning authorized parts. It is also a guide for depot maintenance in establishing initial levels of spare parts.

b. Columns are as follows:

(1) *Source, maintenance, and recoverability code.* Source, maintenance, and recoverability codes indicate the technical service responsible for supply, the maintenance category at which an item is stocked, categories at which an item is installed or repaired, and whether an item is repairable or salvageable. The source code column is divided into four parts.

(*a*) *Column A.* This column indicates the materiel code and designates the area of responsibility for supply. AR 310–1 defines the basic numbers used to identify the materiel code. If the part is Signal materiel responsibility, the column is left blank.

(*b*) *Column B.* This column indicates the point within the maintenance system where the part is available. "PI" indicates that the repair part is a low mortality part; procured by technical services, stocked only in and supplied from technical service *key* depots, and authorized for installation at indicated maintenance categories. "M" applies to repair parts which are not procured or stocked but are to be manufactured by using units at indicated maintenance categories.

(*c*) *Column C.* This column indicates the lowest maintenance categories authorized to install the part.

"O"—Organizational maintenance (operator and organizational)

"F"—Direct support maintenance.

"H"—General support maintenance.

"D"—Depot maintenance.

(*d*) *Column D.* The symbols in this column indicate whether the item is repairable or salvageable, as follows:

"R"—indicates that the part or assembly is economically repairable and is supplied, when available, on an exchange basis.

(2) *Federal stock number.* This column lists the 11-digit Federal stock number.

(3) *Designation by model.* The dagger (†) indicates model in which the part is used.

(4) *Description.* Nomenclature or the standard item name and brief identifying data for each item are listed in this column. When requisitioning, enter the nomenclature and description.

(5) *Unit of issue.* The unit of issue is each unless otherwise indicated and is the supply term by which the individual item is counted for procurement, storage, requisitioning, allowances, and issue purposes.

(6) *Expendability.* Nonexpendable items are indicated by NX. Expendable items are not annotated.

(7) *Quantity incorporated in unit.* This column lists the quantity of each part found in a given assembly, component, or equipment.

(8) *Direct support.* This column indicates quantities of repair parts authorized for initial stockage for use in the direct support maintenance and in supply support to organization. The quantities are based on 100 equipments to be maintained for a 15-day period.

(9) *General support.* The number in this column indicate quantities of repair parts authorized for initial stockage for use in general support maintenance. The quantities are based on 100 equipments to be maintained for a 15-day period.

(10) *Depot.* The numbers in this column indicate quantities of repair parts authorized for depot maintenance and for initial stockage for maintenance, and for supply support to lower categories. The entries are based on the quantity required for rebuild of 100 equipments.

(11) *Illustration.* The "Item No." column lists the reference symbols used for identification of the items in the illustration or text of the manual.

2. Parts for Maintenance

When this equipment is used by signal service organizations organic to the theater headquarters or communication zones to provide thearter communications, those repair parts authorized up to and including general support are authorized for stockage by the organization operating this equipment.

3. Additional Repair Parts Authorization

An asterisk (*) indicates that an item is not authorized for stockage but if required, may be requisitioned for immediate use only.

4. Electron Tubes

The consumption rates given for tubes are conservative theoretical estimates and are provided for use only when more complete information, such as data based on operating experience, is not available. These figures are based on levels and requirements for equipment actually in use, not on authorizations or equipment stored in depots.

5. Requisitioning Information

a. The allowance factors are based on 100 equipments. In order to determine the number of parts authorized for initial stockage for the specific number of equipments supported, the following formula will be used and carried out to two decimal places.

$$\text{Specific number of equipments supported} \times \frac{\text{allowance factor}}{100} = \text{Number of parts authorized for initial stockage.}$$

b. Fractional values obtained from above computation will be rounded to whole numbers as follows:

(1) When the total number of parts authorized is less than 0.5, the quantity authorized will be zero.

(2) When the total number of parts authorized is between 0.5 and 1.0, the quantity authorized will be one.

(3) For all values above one, fractional values below 0.5 will revert to the next lower whole number and fractional value 0.5 and above will advance to the next higher whole number.

c. The quantities determined in accordance with the above computation represent the initial stockage for a 15-day period.

6. References

A maintenance allocation chart is contained in TM 11–5820–335–20. A basic issue items list is contained in TM 11–5820–335–10. Additional instructions concerning maintenance of this equipment is contained in TM 11–5820–335–20P.

7. Reporting of Equipment Manual Improvements

The direct reporting of errors, omissions, and recommendations for improving this equipment manual by the individual user is authorized and encouraged. DA Form 2028

will be used for reporting these improvements. This form may be completed using pencil, pen, or typewriter. DA Forms 2028 will be completed by the individual using the manual and forwarded direct to: Commanding General, U. S. Army Electronics Command, ATTN: AMSEL-MR-(NMP)-MA, Fort Monmouth, New Jersey 07703.

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			TRANSMITTER, RADIO T-195/GRC-19, T-195A/GRC-19, T-195B/GRC-19								
	5820-503-3428		TRANSMITTER, RADIO T-195/GRC-19, T-195A/GRC-19, T-195B/GRC-19: A1, A3 type of emission 100 w max power output; 1.5 to 20.0 mc freq, 10 bands, 8 channels; power output 28.5 v; Sig Dwg SM-C-143281		NX	1					
			NOTE: Model column 1 refers to T-195/GRC-19; model column 2 refers to T-195A/GRC-19; model column 3 refers to T-195B/GRC-19.								
			GROUP I TRANSMITTER, RADIO T-195/GRC-19, T-195A/GRC-19, T-195B/GRC-19								
P1 F	6145-265-6190	† † †	CABLE, SPECIAL PURPOSE, ELECTRICAL: 2 cond, No. 18 AWG; stranded; MIL type CO-212	Ft		11	0.2	0.1	44.0		
P1 F	5935-780-2627	† † †	CONNECTOR, PLUG, ELECTRICAL: 2 male cont; Amphenol #164-42FS(531)			1	0.2	0.1	4.0		
			GROUP II AMPLIFIER, ELECTRONIC CONTROL								
9 P1 H R	5950-568-4786	† † †	AMPLIFIER, ELECTRONIC GROUP: Antenna Network Servo-Amplifier; 2 output channels, 115 v and 6.3 vac, 400 cyc, 1 ph, 250 vdc input		NX	1		1.0	2.0		
M D			CABLE ASSEMBLY: approx 16 in o/a; Sig Dwg SM-D-143420			1					
P1 F	5910-270-5384	† † †	CAPACITOR, FIXED, MICA DIELECTRIC: 510 uuf, ±10%, 300 vdc; Electro Motive #605 (Authorized allowances based on a total of 3 per equip)			2	1.0	0.7	9.0		C905,917
P1 F	5910-668-6149	† † †	CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 100 vdc; Sprague #196P103D3184 (Authorized allowances based on a total of 4 per equip)			2	1.0	0.8	12.0		C904,916

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-284-4114	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 300 vdc; Sprague #96P1030S2			2	1.0	0.5	6.0		C907,919
	P1	F		5910-667-5383	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, 20%, 300 vdc; Sprague #96P10303S4 (Authorized allowances based on a total of 6 per equip)			2	1.0	0.5	18.0		C909,910
	P1	F		5910-809-4721	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 15,000 uuf, ±20%, 300 vdc; Sprague #96P153038 4			2	1.0	0.5	6.0		C913,915
	P1	F		5910-668-6143	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 3300 uuf, ±20%, 100 vdc; Sprague #196P3301S4			2	1.0	0.5	6.0		C903,914
	P1	F		5910-668-5908	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 47,000 uuf, ±20%, 100 vdc; Sprague #186P47301T15			4	1.0	0.9	12.0		C901,902, 911,912
	P1	F		5910-667-5203	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 68,000 uuf, ±10%, 300 vdc; Sprague #86P6839S10			1	1.0	0.5	3.0		
	P1	F		5910-667-5392	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 330,000 uuf, ±20%, 300 vdc; Sprague #186P3340S5			3	1.0	0.5	9.0		C921,922, 923
	P1	F		5910-262-8522	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 470,000 uuf, ±20%, 100 vdc; Sprague #86P474018 5			1	1.0	0.4	3.0		C920
	P1	F		5910-666-7498	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 470,000 uuf, ±20%, 300 vdc; Sprague #86P4740S5 (Authorized allowances based on a total of 4 per equip)			2	1.0	0.8	12.0		C908,918
	P1	O		5820-396-3212	†	†	†				CAP, ELECTRICAL: for chopper; Electronic G901; Sig Dwg SM-C-143399 (Authorized allowances based on a total of 3 per equip)			1	1.0	0.7	9.0		
	M	D			†	†	†				CHASSIS: Amplifier electronic control; Sig Dwg SM-B-143411			1					
	P1	O		5945-709-6017	†	†	†				CHOPPER, ELECTRONIC: transistorized, 1-5/8 in lg x 3/4 in dia; Stewart Warner #G576957			1	1.0	0.4	3.0		G901
	M	D			†	†	†				CLAMP, CABLE: 3/4 in lg x 9/32 in w x 3/8 in h; Sig Dwg SM-B-143421			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			†	†	†				CLAMP, LOOP: Sig dwg SM-D-143396-22			1					
	M	D				†	†	†			CLIP, ELECTRICAL: 3/16 in lg x 3/16 in w x .2655 in h; Sig dwg SM-B-143412-1			2					
	M	D				†	†	†			CLIP, ELECTRICAL: .195 in h x 5/32 in lg x .172 in w; Sig dwg SM-B-143423			5					
	Pl	F		5935-295-5006		†	†	†			CONNECTOR, RECEPTACLE, ELECTRICAL: 15 rd male cont; Sig dwg SM-C-283194 (Authorized allowances based on a total of 3 per equip)			1	1.0	0.7	9.0		P901
	M	D				†	†	†			COVER, ELECTRICAL CONNECTOR: Sig dwg SM-B-143422			1					
	M	D				†	†	†			COVER, ELECTRICAL CONNECTOR: 2-19/32 in lg x 2-1/16 in w x 2-5/32 in thk; Sig dwg SM-B-143401			1					
	Pl	O		5960-193-5145		†	†	†			ELECTRON TUBE: MIL #5751 (Authorized allowances based on a total of 3 per equip)			2	9.9	5.1	300.0		V901,903
	Pl	O		5960-537-3966		†	†	†			ELECTRON TUBE: MIL #6005/6AQ5/6095 (Authorized allowances based on a total of 3 per equip)			2	9.9	5.1	300.0		V902,904
	M	D				†	†	†			POST, BINDING: .601 in lg x 1/4 in dia; 4-40-NC-2B ea end; Sig dwg SM-B-143416			2					
	M	D				†	†	†			POST, BINDING: 1.109 in lg x .312 in dia; Sig dwg SM-B-143413			2					
	M	D				†	†	†			POST, BINDING: 1.422 in lg x .375 in hex; Sig dwg SM-B-143397-1			1					
	M	D				†	†	†			POST, BINDING: 1-5/16 in lg x 3/16 in hex; Sig dwg SM-B-143400			2					
	M	D				†	†	†			POST, BINDING: Sig dwg SM-B-143405			1					
	Pl	F		5945-259-5898		†	†	†			RELAY, ARMATURE: dpdt, 2 amp, 28 vdc, 115 vac; Sig dwg SM-C-143408 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		K901

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5905-279-1945	†	†	†				RESISTOR, FIXED, COMPOSITION: 18 ohm, ±5%, 2 w; MIL #RC42GF180J			1	1.0	0.5	3.0		R931
	P1	F		5905-279-1923	†	†	†				RESISTOR, FIXED, COMPOSITION: 270 ohm, ±10%, 2 w; MIL #RC42GF271K (Authorized allowances based on a total of 3 per equipment)			2	1.0	0.7	9.0		R912,928
	P1	F		5905-195-6817	†	†	†				RESISTOR, FIXED, COMPOSITION: 1000 ohm, ±10%, 1/2 w; MIL #RC20GF102K (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		R917
	P1	F		5905-279-2672	†	†	†				RESISTOR, FIXED, COMPOSITION: 1800 ohm, ±10%, 1/2 w; MIL #RC20GF182K (Authorized allowances based on a total of 3 per equip)			1	1.0	0.7	9.0		R930
	P1	F		5905-195-6502	†	†	†				RESISTOR, FIXED, COMPOSITION: 3300 ohm, ±10%, 1/2 w; MIL #RC20GF332K (Authorized allowances based on a total of 3 per equip)			2	1.0	0.7	9.0		R909,925
	P1	F		5905-195-6752	†	†	†				RESISTOR, FIXED, COMPOSITION: 3900 ohm, ±5%, 2 w; MIL# RC42GF392J			1	1.0	0.5	3.0		R929
	P1	F		5905-279-2295	†	†	†				RESISTOR, FIXED, COMPOSITION: 6800 ohm, ±10%, 2 w; MIL #RC42GF682K			1	1.0	0.5	3.0		R934
	P1	F		5905-185-8521	†	†	†				RESISTOR, FIXED, COMPOSITION: 10,000 ohm, ±10%, 2 w; MIL #RC42GF103K			1	1.0	0.5	3.0		R913
	P1	F		5905-171-2004	†	†	†				RESISTOR, FIXED, COMPOSITION: 22,000 ohm, ±5%, 1/2 w; MIL #RC20GF223J (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		R908
	P1	F		5905-258-6557	†	†	†				RESISTOR, FIXED, COMPOSITION: 27,000 ohm, ±10%, 1w; MIL #RC32GF273K			1	1.0	0.5	3.0		R934
	P1	F		5905-195-6758	†	†	†				RESISTOR, FIXED, COMPOSITION: 27,000 ohm, ±10%, 1/2 w; MIL #RC20GF273K (Authorized allowances based on a total of 8 per equip)			4	1.0	1.2	24.0		R901,904, 915, 918
	P1	F		5905-192-3988	†	†	†				RESISTOR, FIXED, COMPOSITION: 56,000 ohm, ±10%, 1/2 w; MIL #RC20GF563K (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		R914

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5905-195-6761	†	†	†				RESISTOR, FIXED, COMPOSITION: 100,000 ohm, ±5%, 1/2 w; MIL #RC20GF104J (Authorized allowances based on a total of 5 per equip)			2	1.0	0.9	15.0		R903,920
	P1	F		5905-192-9260	†	†	†				RESISTOR, FIXED, COMPOSITION: 150,000 ohm, ±10%, 1/2 w; MIL #RC20GF154K (Authorized allowances based on a total of 3 per equip)			1	1.0	0.7	9.0		R902
	P1	F		5905-295-3409	†	†	†				RESISTOR, FIXED, COMPOSITION: 220,000 ohm, ±10%, 1/2 w; MIL #RC20GF224K (Authorized allowances based on a total of 10 per equip)			5	2.0	1.4	30.0		R906,910, 921,922, 926
	P1	F		5905-185-6946	†	†	†				RESISTOR, FIXED, COMPOSITION: 470,000 ohm, ±10%, 1/2 w; MIL #RC20GF474K (Authorized allowances based on a total of 9 per equip)			4	1.9	1.3	27.0		R907,911 923,927
	P1	F		5905-221-5840	†	†	†				RESISTOR, FIXED, COMPOSITION: 560,000 ohm, ±10%, 1/2 w; MIL #RC20GF564K			1	1.0	0.5	3.0		
	P1	F		5905-192-3982	†	†	†				RESISTOR, FIXED, COMPOSITION: 1 meg, ±10%, 1/2 w; MIL #RC20GF105K (Authorized allowances based on a total of 3 per equip)			2	1.0	0.7	9.0		R905,919
	P1	F		5905-173-6018	†	†	†				RESISTOR, FIXED, WIREWOUND: 35 ohm, ±5%, 10 w; MIL #RW31G350			1	1.0	0.5	3.0		R932
	P1	F		5960-543-0490	†	†	†				SEMICONDUCTOR DEVICE, DIODE: MIL #1N459			2	1.0	0.5	6.0		CR901,902
	P1	O		5960-295-7652	†	†	†				SHIELD, ELECTRON TUBE: 2-1/4 in lg x .810 in dia x .930 in d; Sig Dwg #SM-C-143429-3 (Authorized allowances based on a total of 4 per equip)			2	1.2	0.8	8.0		E902,904
	P1	O		5960-636-0115	†	†	†				SHIELD, ELECTRON TUBE: 1-15/16 in lg x .950 in dia x 1.065 in d; Sig dwg SM-C-143429-5 (Authorized allowances based on a total of 6 per equip)			2	1.9	1.0	12.0		E901,903
	P1	F		5935-502-4721	†	†	†				SOCKET, ELECTRON TUBE: 7 miniature cont; MIL #TS102P02 (Authorized allowances based on a total of 3 per equip)			1	1.0	0.7	6.0		XG901

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5935-260-0516	†	†	†				SOCKET, ELECTRON TUBE: 7 miniature cont; MIL #TS102P01 (Authorized allowances based on a total of 10 per equip)			2	2.0	1.4	20.0		XV902,904
	P1	F		5935-160-1365	†	†	†				SOCKET, ELECTRON TUBE: 9 cont, naval size; MIL #TS103P01 (Authorized allowances based on a total of 8 per equip)			2	2.0	1.2	16.0		XV901,903
	M	D			†	†	†				TERMINAL BOARD: 4-1/4 in lg x 2-29/64 in w x 7/16 in thk; Sig dwg #SM-B-143417			1					
	P1	F		5950-532-3581	†	†	†				TRANSFORMER, POWER STEPDOWN: 115 vac, 360 to 400 cyc; 1 ph; Sig dwg #SM-C-143406			1	1.0	0.5	2.0		T901
	M	D			†	†	†				WIRING ASSEMBLY: Sig dwg #SM-E-143419			1					
											GROUP III AMPLIFIER, RADIO FREQUENCY								
	P1	H	R	5820-503-3367	†	†	†				AMPLIFIER, RADIO FREQUENCY: 1.5 to 20 mc freq; 80 to 125 w output; 6 vac, 60 cyc, 1 ph; 1000 vdc; Sig dwg #SM-D-143453		NX	1		0.5	3.0		
	M	D			†	†	†				AMPLIFIER, RADIO FREQUENCY: Sig dwg No. SM-D-143576			1					
	M	D			†	†	†				BASE, MOTOR: 1-5/16 in lg x 3/8 in w x 1/8 in thk; Sig dwg #SM-B-143619			1					
	M	D			†	†	†				BRACKET, ANGLE: 1-5/8 in lg x 5/8 in w x 9/16 in h; Sig dwg #SM-B-143467			1					
	M	D			†	†	†				BRACKET, ANGLE: 1-17/64 in lg x 5/8 in w x 1 in h; Sig dwg #SM-B-144449			1					
	M	D			†	†	†				BRACKET, ANGLE: 1/4 in lg x 1/4 in w x 1/4 in h; Sig dwg #SM-B-143645			9					
	M	D			†	†	†				BRACKET, ANGLE: 15/32 in lg x 3/8 in w x 3/8 in h; Sig dwg #SM-B-143466			1					
	M	D			†	†	†				BRACKET, ANGLE: 1-1/4 in lg x 1 in wd x 7/16 in h; Sig dwg #SM-B-143611			1					
	M	D			†	†	†				BRACKET, ANGLE: 1-3/4 in lg x 13/16 in wd x 7/8 in h; Sig dwg #SM-B-143638			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			†	†	†				BRACKET, ANGLE: 7/8 in lg x 11/32 in wd x 3/8 in h; Sig dwg #SM-B-143636			1					
	M	D			†	†	†				BRACKET, ANGLE: 3/4 in lg x 11/32 in wd x 5/16 in h; Sig dwg #SM-B-143600			1					
	M	D			†	†	†				BRACKET, ANGLE: 3/4 in lg x 11/32 in wd x 5/16 in h; Sig dwg #SM-B-143601			1					
	M	D			†	†	†				BRACKET, ANGLE: 2-1/8 in lg x 3/4 in wd x 1/2 in h; Sig dwg #SM-B-143511			1					
	M	D			†	†	†				BRACKET, ANGLE: 2-1/8 in lg x 3/4 in wd x 21/32 in h; Sig dwg #SM-B-143512			1					
	M	D			†	†	†				BRACKET, ANGLE: Sig dwg #SM-B-143559			1					
	M	D			†	†	†				BRACKET, ANGLE: Sig dwg #SM-B-143562			1					
	M	D			†	†	†				BRACKET, ANGLE: Sig dwg #SM-B-143504			1					
	M	D			†	†	†				CABLE ASSEMBLY: Sig dwg #SM-D-143533			1					
	P1	F		5995-280-3028	†	†	†				CABLE ASSEMBLY, RADIO FREQUENCY: 7-1/16 in lg o/a; Sig dwg #SM-C-143604			1	1.0	0.5	3.0		P203
	P	F		5820-396-3212	†	†	†				CAP, ELECTRICAL: for chopper G201; Sig dwg #SM-C-143399 (For authorized allowances see Group II)			1					
	M	D			†	†	†				CAPACITOR ASSEMBLY: 2-1/2 in lg x 2-1/4 in h x 2-3/4 in w; Sig dwg #SM-D-143545			1					
	M	D			†	†	†				CAPACITOR ASSEMBLY: 4-5/8 in lg x 2-3/8 in w x 2-5/8 in h; Sig dwg #SM-C-143571			1					
	P1	F		5910-174-9242	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 7 uuf, ±0.5 uuf, 500 vdc; MIL #CC20CH070D (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		C234
	P1	F		5910-666-7170	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 10 uuf, ±5%, 500 vdc; Electro Motive #CM15D100J			1	1.0	0.5	3.0		C626
	P1	F		5910-809-8658	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 12 uuf, ±5%, 5000 vdc; Centralab #DA850-093			1	1.0	0.5	3.0		C218

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-190-6551	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 18 uuf, ±5%, 500 vdc; Electro Motive #CM15C180J			1	1.0	0.5	3.0		C-224
	P1	F		5910-160-8106	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 20 uuf, ±5%, 500 vdc; MIL #CC30CH200J			1	1.0	0.5	3.0		C235
	P1	F		5910-264-9420	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 22 uuf, ±5%, 500 vdc; Electric Motive #CM15D220J			1	1.0	0.5	3.0		C214
	P1	F		5910-666-8095	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 28 uuf, ±5%, 5000 vdc; Centralab #DA850-085			2	1.0	0.5	6.0		C214,217
	P1	F		5910-811-4393	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 40 uuf, ±4%, 500 vdc; Centralab #DA850-098			1	1.0	0.5	3.0		C215
	P1	F		5910-666-8148	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 50 uuf, ±2%, 5000 vdc; Centralab #850A-150			1	1.0	0.5	3.0		C219
	P1	F		5910-811-4390	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 57 uuf, ±2%, 5000 vdc; Centralab #850A-151			1	1.0	0.5	3.0		C216
	P1	F		5910-811-4391	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 63 uuf, ±2%, 5000 vdc; Centralab #850-059			1	1.0	0.5	3.0		C220
	P1	F		5910-276-6890	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 91 uuf, ±2%, 500 vdc; Electro Motive #605			1	1.0	0.5	3.0		C225
	P1	F		5910-184-1848	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 100 uuf, ±10%, 500 vdc; Electro Motive #CM15D101K			1	1.0	0.5	3.0		C203
	P1	F		5910-666-7928	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 130 uuf, ±2%, 500 vdc; Erie #370FA-130			1	1.0	0.5	3.0		C227
	P1	F		5910-668-3608	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 360 uuf, ±2%, 500 vdc; Erie #370FA-360 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		C228
	P1	F		5910-270-5384	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 510 uuf, ±10%, 300 vdc; Electro Motive #605 (For authorized allowances see Group II)			1					C248
	P1	F		5910-667-5727	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 761 uuf, ±5%, 500 vdc; Erie #370-FA761J			1	1.0	0.5	3.0		C230
	P1	F		5910-667-5563	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 820 uuf, ±2%, 500 vdc; Erie #370			1	1.0	0.5	3.0		C229

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-196-0540	†	†	†				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 1000 uuf, ±20%, 5000 vdc; Sig dwg #SM-D-143595-4			4	1.5	0.8	12.0		C202,205, 250,257
	M	D			†	†	†				BEARING, SLEEVE: .1885 in ID x 15/32 in OD x 11/64 in lg; Sig dwg #SM-C-283156			1					
	P1	F		5910-101-4023	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 1000 uuf, ±10%, 500 vdc; MIL #CM30B102K			1	1.0	0.5	3.0		C201
	P1	F		5910-667-5643	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 1100 uuf, ±2%, 500 vdc; Erie #370-FA			1	1.0	0.5	3.0		C232
	P1	F		5910-668-5933	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 1500 uuf, ±20%, 200 vdc; Sprague #96P152028S2			1	1.0	0.5	3.0		C208
	P1	F		5910-101-3995	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 1500 uuf, ±10%, 500 vdc; MIL #CM30B152K			1	1.0	0.5	3.0		C204
	P1	F		5910-101-4058	†	†	†				CAPACITOR, FIXED, MICA DIELECTRIC: 10,000 uuf, ±10%, 300 vdc; MIL #CM35D103K			1	1.0	0.5	3.0		C247
	P1	F		5910-265-3295	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±10%, 200 vdc; Sprague #75P10392 (Authorized allowances based on a total of 10 per equip)			4	2.0	1.0	30.0		C210,237, 238,239
	P1	F		5910-667-5383	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 300 vdc; Sprague #96P1030384 (For authorized allowances see Group II)			2					C240,242
	P1	F		5910-186-0113	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 22,000 uuf, ±10%, 200 vdc; Sprague #65P22392			1	1.0	0.5	3.0		C236
	P1	F		5910-668-5903	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 47,000 uuf, ±20%, 100 vdc; Sprague #186P47301S15			2	1.0	0.5	6.0		C245,246
	P1	F		5910-270-5343	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 100,000 uuf, ±20%, 100 vdc; Sprague #86P10401S1 (Authorized allowances based on a total of 6 per equip)			1	1.9	1.0	18.0		C249
	P1	F		5910-667-4829	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 150,000 uuf, ±20%, 200 vdc; Sprague #86P1540231			1	1.0	0.5	3.0		C207

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-681-1859	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 220,000 uuf, ±10%, 200 vdc; Sprague #118P2249282			1	1.0	0.5	3.0		C253
	P1	F		5910-519-6998	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 330,000 uuf, ±10%, 120 vdc; Sprague #P66775			1	1.0	0.5	3.0		C241
	P1	F		5910-666-7498	†	†	†				CAPACITOR, FIXED, PAPER DIELECTRIC: 470,000 uuf, ±20%, 300 vdc; Sprague #86P47403S5 (for authorized allowances see Group II)			2					C243,244
	P1	F		5910-846-6783			†				CAPACITOR, FIXED, PAPER DIELECTRIC: 680,000 uuf, ±10%, 200 vdc; Sprague #118P6849282			1	1.0	0.5	2.0		C252
	P1	F		5910-649-4449			†				CAPACITOR, VARIABLE: 2 sect. 13.5 uuf to 77.8 uu max 17 uu min to 99.6 uu max; Collins #926-0130-00			1	1.0	0.5	2.0		C252
	P1	F		5910-667-7223	†	†	†				CAPACITOR, VARIABLE: 2 sect. 23 uuf to 454 uuf, 23 uuf to 491 uuf; Cardwell #X			1	1.0	0.5	2.0		C222
	P1	F		5910-643-6892	†	†	†				CAPACITOR, FIXED ELECTROLYTIC: 4 uf, 60 vdc; Fansteel #PP4B60A2 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	2.0		C209
	M	D				†	†	†			CASE, PLASTIC: Sig dwg #SM-C-143503			1					
	P1	F		5950-322-5077		†	†	†			CHOKE, RF: 27 mc; Jeffers Elect #10404-20			1	1.0	0.5	2.0		L206
	P	O		6130-396-3147		†	†	†			CHOPPER, ELECTROMECHANICAL: Sig dwg #SM-C-143398			1	1.0	0.5	2.0		G201
	P1	F		5975-396-3116		†	†	†			CLAMP: Sig dwg #SM-B-144451			1	1.0	0.5	2.0		
	M	D						†			CLIP, ELECTRICAL: Sig dwg #SM-B-356802			1					
	P1	F		5340-836-1945				†			CLIP, SPRING TENSION: Atlas EE Corp #100 200 57			1	1.0	0.5	2.0		
	M	D				†	†	†			CLIP, ELECTRICAL: .195 in lg x 5/32 in w x .140 in h; Sig dwg #SM-B-143423			8					
	P1	F		5950-395-9232		†	†	†			COIL, RF: 140 turns, 28 AWG wire, single layer wnd; Sig dwg #SM-C-143514			1	1.0	0.5	3.0		L203
	P1	F		5950-301-4495		†	†	†			COIL, RF: 1 wnd, 2 turns, No. 28 AWG wire; Sig dwg #SM-C-143569			1	1.0	0.5	3.0		T201

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5950-696-5530	†	†	†				COIL, RF: 1 wnd, 56 uh; Jeffers Electronic #10404-30			1	1.0	0.5	3.0		L207
	P1	F		5950-393-1467	†	†	†				COIL, RF: 2.2 mh at 350 kc, 4 pie Universal wnd; Sig dwg #SM-C-143376-18 (Authorized allowances based on a total of 3 per equip)			2	1.0	0.7	9.0		L201,205
	P1	F		6105-892-1948			†				COLLAR, MOUNTING: Sig dwg #SM-B-356801			1	0.9	0.5	2.0		
	M	D			†	†	†				COLLAR, SHAFT: 0.312 in ID, 0.562 in OD x 0.218 thk; Sig dwg #SM-B-143483			1					
	P1	F		5935-295-5006	/	/	/				CONNECTOR, RECEPTACLE ELECTRICAL: 15 rd male cont; Sig dwg #SM-C-283194 (For authorized allowances see Group II)			1					P201
	P1	F		5935-696-4753	/	/	/				CONNECTOR, RECEPTACLE, ELECTRICAL: 2 pin cont; Sig dwg #SM-B-143463			1	1.0	0.5	3.0		P204
	P1	F		5930-532-4603	/	/	/				CONTACT ASSEMBLY, ELECTRICAL: 1A1B contact arrangement; 28 vdc, 1/4 amp; Auto Elect #SW45-1778			1	1.0	0.5	2.0		S203
	M	D			/	/	/				COVER: Aluminum alloy; Sig dwg #SM-B-143458			1					
	M	D			/	/	/				COVER: aluminum alloy; Sig dwg #SM-D-143460			1					
	M	D			/	/	/				COVER: aluminum alloy; 9-1/8 in lg x 8-5/16 in w x 7-29/32 in h; Sig dwg #SM-C-143471			1					
	M	D			/	/	/				COVER: aluminum alloy, 7-3/4 in lg x 5-7/32 inw x 7/16 h; Sig dwg #SM-C-143593			1					
	M	D			/	/	/				COVER: aluminum; Sig dwg #SM-D-143595			1					
	M	D			/	/	/				COVER: aluminum; 8-1/4 in lg x 5-5/8 in w x 7/16 in h; Sig dwg #SM-D-143622			1					
	M	D			/	/	/				COVER: 2-1/8 in lg x 1-1/2 in w x .062 in thk; Sig dwg #SM-B-143502			1					
	M	D			/	/	/				COVER: 4-3/4 in lg x 3-13/16 in w x 2-21/32 in h; Sig dwg #SM-C-143454			1					

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
M D		/ / /	COUPLING, SHAFT, RIGID: 1 in dia x 11/32 in thk; Sig dwg #SM-B-143393			1					
M D		/ / /	DECAL: 2-1/8 in lg x 1-3/16 in w; Sig dwg #SM-B-144452			1					
M D		/ / /	DECAL: 1-1/2 in dia x .032 in thk; Sig dwg #SM-B-143509			1					
P1 F	5820-571-1830	/ / /	DUCT, AIR: 2.516 in dia x 1.604 in d approx o/a; Sig dwg #SM-C-143625			1	1.0	0.5	2.0		
P1 O	5960-264-3001	/ / /	ELECTRON TUBE: MIL #4X150D (Authorized allowances based on a total of 3 per equip)			1	19.8	9.9	300.0		V201
P1 O	5960-193-5145	/ / /	ELECTRON TUBE: MIL #5751 (For authorized allowances see Group II)			1					V204
P1 O	5960-188-3915	/ / /	ELECTRON TUBE: MIL #5763 (Authorized allowances based on a total of 2 per equip)			1	32.8	16.4	200.0		V202
P1 O	5960-537-3966	/ / /	ELECTRON TUBE: MIL #6005/6AQ5/6095 (For authorized allowances see Group II)			1					V203
M D		/ / /	FERRULE, ELECTRICAL CONDUCTOR: 1/2 in dia x .150 in thk; Sig dwg #SM-B-170621			1					
M D		/ / /	GEAR ASSEMBLY: c/o 2 spur gears; Sig dwg #SM-B-143547			1					
M D		/ / /	GEAR, ASSEMBLY: spur, 140 teeth; Sig dwg #SM-C-143523			1					
M D		/ / /	GEAR ASSEMBLY: spur, 78 teeth; Sig dwg #SM-C-143541			1					
M D		/ / /	HOUSING, BRASS: 4-13/16 in lg x 3-1/2 in w x .968 in h; Sig dwg #SM-D-143640			1					
M D		/ / /	HOLDER: 13/16 in lg x 1/2 in w x 17/32 in h; Sig dwg #SM-C-143522			1					
M D		/ / /	HUB, GEAR: 7/16 in dia x 5/32 in thk; Sig dwg #SM-B-143508			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				HUB, GEAR: 13/32 in dia x 19/32 in thk; Sig dwg #SM-B-143549			1					
	M	D			/	/	/				INSERT, BRASS: 3/16 in dia x 3/16 in thk; Sig dwg #SM-B-143478			2					
	M	D			/	/	/				INSULATOR, DISK: 1/2 in dia x 1/32 in thk; Sig dwg #SM-B-143643			1					
	M	D			/	/	/				INSULATOR, PLATE: 1-5/8 in lg x 1/2 in w x 3/32 in thk; Sig dwg #SM-B-143466			1					
	M	D			/	/	/				INSULATOR, PLATE: Plastic, 1.014 in lg x 7/8 in w x 3/32 in thk; Sig dwg #SM-B-144448			1					
	M	D					/				MOTOR, ASSEMBLY: ac; Sig dwg #SM-C-357260			1					
	P1	F		6615-322-5365	/	/	/				MOTOR, CONTROL: 400 cyc, 115 v, 0.260 amp, 1030 ohm; Kearfoot #R-110-2B-C; SM-C-143520 (Authorized allowances based on a total of 3 per equip)			1	1.0	0.7	6.0		B201
	P1	F		6105-846-2365			/				MOTOR, ALTERNATING CURRENT: 50 v, 400 cyc, single phase; Eastern Air Devices #2345HKS-1; SM-C-283622			1	1.0	0.5	2.0		B202
	P1	F		6105-548-2565	/	/					MOTOR, DIRECT CURRENT: 27.5 v, 0.8 amp, 1/1000 hp, 12,000 rpm; Globe Ind. # MMB			1	1.0	0.5	2.0		B202
	M	D			/	/	/				MOUNTING ASSEMBLY: Sig dwg #SM-C-143558			1					
	M	D			/	/	/				MOUNTING: 8-7/32 in lg x 7-13/16 in w x 5/16 in thk; Sig dwg #SM-D-143475			1					
	M	D			/	/	/				MOUNTING: Sig dwg #SM-D-143566			1					
	M	D			/	/	/				MOUNTING: Sig dwg #SM-B-143561			1					
	P1	F		5330-729-4605	/	/	/				PACKING COMPOUND: rubber, 19-5/8 in lg x 7/32 in w x 8/16 in thk; Sig dwg #SM-B-143641			1	1.0	0.5	2.0		
	M	D			/	/	/				PLATE, ASSEMBLY: Sig dwg #SM-D-143477			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
																		FIGURE NO.	ITEM NO.
A	B	C	D																
											T-195/GRC-19 (continued)								
	M	D			/	/	/				PLATE, ASSEMBLY: Sig dwg #SM-D-143585			1					
	M	D			/	/	/				PLATE: brass, 4-13/64 in lg x 3-1/2 in w x 11/64 in thk; Sig dwg #SM-D-143649			1					
	M	D			/	/	/				PLATE: aluminum alloy, 2-5/8 in lg x 2-9/32 in w; Sig dwg #SM-C-143613			1					
	M	D			/	/	/				PLATE: aluminum alloy, 8-5/16 in lg x 23/32 in w x .64 in thk; Sig dwg #SM-C-143469			1					
	M	D			/	/	/				PLATE: aluminum alloy, 2 in lg x 25/32 in w x 0.64 in thk; Sig dwg #SM-B-143579			1					
	M	D			/	/	/				PLATE: aluminum alloy, 3-3/16 in lg x 23/32 in w x .125 in thk; Sig dwg #SM-B-143552			1					
	M	D			/	/	/				PLATE: aluminum alloy, 2-17/32 in lg x 2-7/32 in w x .125 in thk; Sig dwg #SM-B-143573			1					
	M	D			/	/	/				PLATE: aluminum alloy, 2-7/8 in lg x 2-13/16 in w x 0.95 in thk; Sig dwg #SM-B-143527			1					
	M	D			/	/	/				PLATE: aluminum alloy, 8-1/4 in lg x 5-5/8 in w x 0.187 in thk; Sig dwg #SM-C-143527			1					
	M	D			/	/	/				PLATE: aluminum alloy, 3-5/16 in lg x 2-13/16 in w x 0.90 in thk; Sig dwg #SM-B-143591			1					
	M	D					/				PLATE ASSEMBLY, MOUNTING: Sig dwg #SM-C-356800			1					
	M	D					/				PLATE, MOUNTING: Sig dwg #SM-C-357268			1					
	M	D					/				PLATE, MOUNTING: Sig dwg #SM-C-357279			1					
	M	D			/	/	/				PLUG: Sig dwg #SM-B-143546			1					
	M	D			/	/	/				PLUG: Sig dwg #SM-B-143572			1					
	P1	F		5935-201-8579	/	/	/				PLUG, TIP: std phone tip, cont element; 7/8 in lg o/a; Sig dwg #SM-B-143534 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	4.0		P205

SOURCE CODE A B C D	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION FIGURE NO.	ILLUSTRATION ITEM NO.
			T-195/GRC-19 (continued)								
P L F	5935-500-5039	/ / /	PLUG, TIP: med phone tip cont element, 7/8 in lg o/a; Sig dwg #SM-B-143535 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	4.0		P206
M D		/ / /	POINTER, DIAL: 1/2 in lg x 11/32 in w x .015 in thk; Sig dwg #SM-B-143590			1					
P L F	5970-284-8725	/ / /	POST, BINDING: Jan type #NS5W0108			2	1.0	0.5	4.0		
P L F	5945-259-6446	/ / /	RELAY, ARMATURE: cont arrangement 1A; 27.5 v, 0.575 amp; Sig dwg #SM-C-143770			1	1.0	0.5	3.0		K201
P L F	5945-808-9755	/ / /	RELAY, ARMATURE: cont arrangement 2B; 32 v, .1104 amp; Sig dwg #SM-C-143505			1	1.0	0.5	3.0		K203
P L F	5945-696-4862	/ / /	RELAY, THERMAL: spst, 28 v, 5 amp; Sig dwg #SM-C-143596			1	1.0	0.5	3.0		K202
P L F	5905-264-7117	/ / /	RESISTOR, FIXED, W/W: 7.10 ohm, ±5%, 8 w; MIL #RW30G7R1			1	1.0	0.5	3.0		R240
P L F	5905-636-7780	/ / /	RESISTOR, FIXED, W/W: 16 ohm, ±5%, 14 w; MIL #RE31V160			1	1.0	0.5	3.0		R239
P L F	5905-845-8404	/	RESISTOR, FIXED, FILM: 23.7 ohm, ±1%, 1/8 w; IRC-MDA 23.7 ohm			2	1.0	0.5	6.0		R241,242
P L F	5905-242-7662	/ / /	RESISTOR, FIXED, W/W: 45 ohm, ±5%, 8 w; MIL #RW30G450			1	1.0	0.5	3.0		R235
P L F	5905-279-2643	/ / /	RESISTOR, FIXED, COMPOSITION: 100 ohm, ±5%, 1 w; MIL #RC32GF101J (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		R208
P L F	5905-171-1975	/ / /	RESISTOR, FIXED, COMPOSITION: 150 ohm, ±5%, 2 w; MIL #RC42GF151J			2	1.0	0.5	6.0		R206,207
P L F	5905-549-8902	/ / /	RESISTOR, FIXED, W/W: 220 ohm, ±5%, 8 w; MIL #RW30221			1	1.0	0.5	3.0		R234
P L F	5905-279-1923	/ / /	RESISTOR, FIXED, COMPOSITION: 270 ohm, ±10%, 2w; MIL #RC42GF271K (For authorized allowances see Group II)			1					R214

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5905-279-2546	/	/	/				RESISTOR, FIXED, COMPOSITION: 360 ohm, ±5%, 1 w; MIL #RC32GF361J			1	1.0	0.5	3.0		R201
	P1	F		5905-279-2642	/	/	/				RESISTOR, FIXED, COMPOSITION: 390 ohm, ±5%, 1 w; MIL #RC32GF391J			1	1.0	0.5	3.0		R205
	P1	F		5905-284-3745	/	/	/				RESISTOR, FIXED, W/W: 400 ohm, ±5%, 8 w; MIL #RW3G401 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		R236
	P1	F		5905-686-0082			/				RESISTOR, FIXED, FILM: 2370 ohm, ±1%, 1/8 w; IRC-MDA-2.37K ohm			1	1.0	0.5	3.0		R243
	P1	F		5905-195-6741	/	/	/				RESISTOR, FIXED, COMPOSITION: 2700 ohm, ±10%, 1/2 w; MIL #RC20GF272K			1	1.0	0.5	3.0		R230
	P1	F		5905-195-6502	/	/	/				RESISTOR, FIXED, COMPOSITION: 3300 ohm, ±10%, 1/2 w; MIL #RC20GF332K (For authorized allowances see Group II)			1					R221
	P1	F		5905-195-6453	/	/	/				RESISTOR, FIXED, COMPOSITION: 5600 ohm, ±5%, 1/2 w; MIL #RC20GF562J			2	1.0	0.5	6.0		R209,210
	P1	F		5905-100-7222	/	/	/				RESISTOR, FIXED, W/W: 8000 ohm ±5%, 18 w; MIL #RW33G802			3	1.0	0.7	9.0		R202,224, 228
	P1	F		5905-171-2004	/	/	/				RESISTOR, FIXED, COMPOSITION: 22,000 ohm, ±5%, 1/2 w; MIL #RC20GF223J (For authorized allowances see Group II)			1					R217
	P1	F		5905-195-6758	/	/	/				RESISTOR, FIXED, COMPOSITION: 27000 ohm, ±10%, 1/2 w; MIL #RC20GF273K (For authorized allowances see Group II)			2					R225,227
	P1	F		5905-120-0487	/	/	/				RESISTOR, FIXED, COMPOSITION: 33,000 ohm, ±10%, 1 w; MIL #RC32GF333K (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		R233
	P1	F		5905-102-2444	/	/	/				RESISTOR, FIXED, COMPOSITION: 47,000 ohm, ±10%, 1 w; MIL #RC32GF473K			1	1.0	0.5	3.0		R237
	P1	F		5905-254-9201	/	/	/				RESISTOR, FIXED, COMPOSITION: 47,000 ohm, ±5%, 1/2 w; MIL #RC20GF473J			2	1.0	0.5	6.0		R222,223
	P1	F		5905-295-3410	/	/	/				RESISTOR, FIXED, COMPOSITION: 47,000 ohm, ±10%, 1/2 w; MIL #RC20GF473K (Authorized allowances based on a total of 3 per equip)			1	1.0	0.7	9.0		R216

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5905-254-7097	/	/	/				RESISTOR, FIXED, COMPOSITION: 82,000 ohm, ±10%, 1/2 w; MIL #RC20GF823K			1	1.0	0.5	3.0		R231
	P1	F		5905-195-6761	/	/	/				RESISTOR, FIXED, COMPOSITION: 100,000 ohm, ±5%, 1/2 w; MIL #RC20GF104J (For authorized allowances see Group II)			2					R203
	P1	F		5905-192-9260	/	/	/				RESISTOR, FIXED, COMPOSITION: 150,000 ohm, ±10%, 1/2 w; MIL #RC20GF154K (For authorized allowances see Group II)			1					R212
	P1	F		5905-295-3409	/	/	/				RESISTOR, FIXED, COMPOSITION: 220,000 ohm, ±10%, 1/2 w; MIL #RC20GF224K (For authorized allowances see Group II)			2					R215,218
	P1	F		5905-249-9490	/	/	/				RESISTOR, FIXED, COMPOSITION: 270,000 ohm, ±5%, 1/2 w; MIL #RC20GF274J			1	1.0	0.5	3.0		R232
	P1	F		5905-185-6946	/	/	/				RESISTOR, FIXED, COMPOSITION: 470,000 ohm, ±10%, 1/2 w; MIL #RC20GF474K (For authorized allowances see Group II)			3					R213,219, 220
	P1	F		5905-221-5849	/	/	/				RESISTOR, FIXED, COMPOSITION: 820,000 ohm, ±10%, 1/2 w; MIL #RC20GF824K			3	1.0	0.7	9.0		R204,211, 229
	M	D			/	/	/				RING, RETAINING: 2-5/8 in dia x .290 in thk; Sig dwg #SM-B-143632			1					
	M	D			/	/	/				RING, RETAINING: 2-1/2 in lg x 1-1/8 in w x 3/4 in thk; Sig dwg #SM-C-143631			1					
	P1	F		5340-598-1231	/	/	/				RING, RETAINING: .114 in ID x 0.025 in thk; Waldes #5133-15			1	1.0	0.5	2.0		H206
	P1	F		5340-282-0813	/	/	/				RING, RETAINING: 1.45 in ID x 0.025 in thk; Waldes #5133-18 (Authorized allowances based on a total of 16 per equip)			2	2.0	1.0	32.0		
	P1	F		5340-286-9458	/	/	/				RING, RETAINING: .207 in ID x 0.025 in thk; Waldes #5133-25			2	1.0	0.5	4.0		
	P1	F		5305-754-3173	/	/	/				SCREW, CAPTIVE, SOCKET HEAD: 4-40 NC 2A; 1/2 in lg; Sig dwg #SM-D-143477-17 (Authorized allowances based on a total of 11 per equip)			1	2.0	1.2	22.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				SCROLL: brass, 1-7/8 in lg x 1-3/4 in w x .968 in thk; Sig dwg #SM-D-143647			1					
	P	F		5960-780-2609	/	/	/				SEMICONDUCTOR DEVICE, SET: 777 attached pair; Philco #354-1809-1 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		CR201,202
	M	D			/	/	/				SHAFT, SHOULDER, STRAIGHT: 7.843 in lg x .249 in dia; Sig dwg #SM-B-143484			1					
	M	D			/	/	/				SHIELD, COVER: 1 in sq x 3/4 in h; Sig dwg #SM-B-144446			1					
	M	D			/	/	/				SHIELD, COIL: 1-1/16 in lg x 7/8 in w x .062 in thk; Sig dwg #SM-B-143513			4					
	M	D			/	/	/				SHIELD, ELECTRICAL PLATE: 2 in dia x .014 in thk; Sig dwg #SM-C-143476			5					
	P	O		5960-295-7652	/	/	/				SHIELD, ELECTRON TUBE: 2-1/4 in lg x .810 in dia x .930 in d; Sig dwg #SM-C-143429-3 (For authorized allowances see Group II)			1					E223
	P	O		5960-636-0115	/	/	/				SHIELD, ELECTRON TUBE: 1-15/16 in lg x .950 in dia x 1.065 in d; Sig dwg #SM-C-143429-5 (For authorized allowances see Group II)			1					E224
	P	O		5960-284-4352	/	/	/				SHIELD, ELECTRON TUBE: 2-3/8 in lg x .950 in dia x 1.065 in d; Sig dwg #SM-C-143429-6 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	2.0		E222
	M	D			/	/	/				SHIM, ALUMINUM ALLOY: 1.046 in dia x .032 in thk; Sig dwg #SM-B-143615			1					
		F		5935-502-4721	/	/	/				SOCKET, ELECTRON TUBE: 7 miniature cont; MIL #TS-102P02 (For authorized allowances see Group II)			1					XG201
		F		5935-260-0516	/	/	/				SOCKET, ELECTRON TUBE: 7 miniature cont; MIL #TS-102P01 (For authorized allowances see Group II)			1					XV203

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
		F		5935-160-1365	/	/	/				SOCKET, ELECTRON TUBE: 9 cont, Novel size; MIL #TS103P01 (For authorized allowances see Group II)			2					XV202,204
	P1	F		5935-696-4735	/	/	/				SOCKET, ELECTRON TUBE: 8 pin; Eitel-McCulloug #Y-101 (Authorized allowances based on a total of 3 per equip)			1	1.0	0.5	2.0		XV201
	M	D			/	/	/				SPACER, SLEEVE: 7/16 in dia x 3/16 in thk; Sig dwg #143598			1					
	M	D			/	/	/				SPACER, SLEEVE: 1/4 in dia x 3/8 in lg; Sig dwg #SM-B-143580			2					
	M	D			/	/	/				SPACER, SLEEVE: 1/2 in dia x .078 in thk; Sig dwg #SM-B-143528			1					
	M	D			/	/	/				SPACER, SLEEVE: 1/4 in dia x .281 in thk; Sig dwg #SM-B-143586			2					
	M	D			/	/	/				SPACER, SLEEVE: 1/4 in dia x .531 in lg; Sig dwg #SM-B-143587			2					
	M	D			/	/	/				SPACER, SLEEVE: .312 in dia x .282 in thk; Sig dwg #SM-B-143493			3					
	M	D			/	/	/				SPACER, SLEEVE: .312 in dia x .672 in lg; Sig dwg #SM-B-143494			3					
	M	D			/	/	/				SPRING, STEEL WIRE: 1/4 in lg x 5/32 in w x .035 in dia; Sig dwg #SM-B-144477			1					
	M	D					/				STRAP, LEAD: Sig dwg #SM-B-356809			1					
	M	D			/	/	/				STRAP, RETAINER: 1-1/2 in lg x 5/8 in w x .064 in thk; Sig dwg #SM-B-143461			2					
	M	D			/	/	/				STRAP, RETAINER: 7/8 in lg x 3/16 in w x .020 in thk; Sig dwg #SM-B-143564			1					
	M	D			/	/	/				STRAP, RETAINER: 2-1/2 in lg x 1 in w x .090 in thk; Sig dwg #SM-B-143588			1					
	M	D			/	/	/				STRAP, RETAINER: 4 in lg x 1-3/16 in w x .032 in thk; Sig dwg #SM-B-143495			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				STRAP, RETAINER: 2-3/16 in lg x 5/16 in w x 0.020 in thk; Sig dwg #SM-B-143496			1					
	M	D			/	/	/				STRAP, RETAINER: 1-1/2 in lg x 5/16 in w x .020 in thk; Sig dwg #SM-B-143497			1					
	M	D					/				STRIP, TERMINAL: Sig dwg #SM-C-357272			1					
	M	D			/	/	/				STUD: 6-32 NC-2A x 9/32 in ea end; 21/32 in lg o/a; Sig dwg #SM-B-143498			10					
	M	D			/	/	/				SUPPORT ASSEMBLY: Sig dwg #SM-B-143627			1					
	M	D			/	/	/				SUPPRESSOR ASSEMBLY: 1-1/4 in lg x 1 in w; Sig dwg #SM-B-143609			1					
	P1	F		5915-501-4017	/	/	/				SUPPRESSOR, PARASITIC: 8 coils #20 AWG wire, 27/32 in lg x 11/32 in dia; Sig dwg #SM-B-143607			1	1.0	0.5	2.0		E201
	P1	F		5930-755-3928	/	/	/				SWITCH, ROTARY: 1 moving cont, 18 fixed cont 1 pole, 7.5 amp, 115 vac; Sig dwg #SM-B-143480			2	1.0	0.5	8.0		S201B, S201D
	P1	F		5930-752-2995	/	/	/				SWITCH, ROTARY: 1 moving cont, 18 fixed cont, 1 pole, 7.5 amp, 115 vac; Sig dwg #SM-B-143479			1	1.0	0.5	4.0		S201C
	P1	F		5930-755-3927	/	/	/				SWITCH, ROTARY: 1 moving cont, 18 fixed , 1 pole, 7.5 amp, 115 vac; Sig dwg #SM-B-143481			1	1.0	0.5	4.0		S201A
	P1	F		5930-538-6133	/	/	/				SWITCH, ROTARY: dp, 2 moving cont, 13 fixed cont; Sig dwg #SM-B-143771			1	1.0	0.5	4.0		S201E
	P1	F		5930-696-6761	/	/	/				SWITCH, THERMOSTATIC: spst, normally closed; -40° C to 85°C; Sig dwg #SM-B-143634			1	1.0	0.5	4.0		S202
	M	D			/	/	/				TERMINAL BOARD: 3-7/32 in lg x 2-5/8 in w x 3/37 in thk; Sig dwg #SM-C-143557			1					
	M	D					/				TERMINAL BOARD: Sig dwg #SM-C-357263			1					E223
	M	D					/				TERMINAL BOARD: Sig dwg #SM-D-357532			1					
	P	F		5950-395-9231	/	/	/				TRANSFORMER, RADIO FREQUENCY: 165 turns #28 AWG wire, tapped at 87-1/2 in turns; Sig dwg #SM-C-143518			1	1.0	0.5	3.0		L202

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5950-537-5121	/	/	/				TRANSFORMER, RF: 41 turns #14 AWG wire; Sig dwg #SM-C-143567			1	1.0	0.5	3.0		L204
	P1	F		5950-757-2080			/				TRANSFORMER, TOROIDAL: Sig dwg #SM-D-357568			1	1.0	0.5	3.0		T202
	P1	F		5960-853-5975			/				TRANSISTOR: Clevite Corp #CTP1730			2	1.0	0.5	6.0		Q201,202
	M	D			/	/	/				WHEEL DETENT: 1-1/2 in dia x .312 in thk; Sig dwg #SM-C-143500			1					
	M	D			/	/	/				WIRING ASSEMBLY: Sig dwg #SM-E-143551			1					
											GROUP IV CONTROL, ANTENNA TUNING								
	P1	H	R	5820-284-4268	/	/	/				CONTROL, ANTENNA: antenna tuning capacitor assy, 115 v, 400 cyc, 1 ph; Sig dwg #SM-D-143650		NX	1		0.5	2.0		
	M	D			/	/	/				ARM, ASSEMBLY: 1-41/64 in lg x 5/16 in w x .312 in thk; Sig dwg #SM-B-143668			1					
	M	D			/	/	/				ARM, GEAR ACTUATOR: 1-41/64 in lg x 5/16 in w x .312 in thk; Sig dwg #SM-B-143669			1					
	M	D			/	/	/				BAR: plastic, 1-1/2 in lg x .187 in w x 3/16 in thk; Sig dwg #SM-B-143722			1					
	M	D			/	/	/				BAR: aluminum, 2-7/16 in lg x 5/8 in w x 3/16 in thk; Sig dwg #SM-143655			1					
	M	D			/	/	/				BLADE, SWITCH: 1-7/8 in lg x 3/8 in w x .015 in thk; Sig dwg #SM-B-356708			1					
	M	D			/	/	/				BOARD AND RACK ASSEMBLY: Sig dwg #SM-C-357200			1					
	M	D			/	/	/				BRACKET, ANGLE: 3-1/8 in lg x 1-1/8 in w x 9/16 in thk; Sig dwg #SM-C-143684			1					
	M	D			/	/	/				BUSHING, MACHINE THREAD: .187 in lg x 3/8-32 NEF-3A; Sig dwg #SM-B-143665			1					
	P1	F		5910-127-1652	/	/	/				CAPACITOR, FIXED, MICA DIELECTRIC: 100 uuf, ±5%, 500 vdc; Erie #370FA			1	1.0	0.5	3.0		C1009

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-667-5674	/	/	/				CAPACITOR, FIXED, MICA DIELECTRIC: 280 uuf, ±20%, 500 vdc; Erie #370FA			1	1.0	0.5	3.0		C1004
	P1	F		5910-668-3608	/	/	/				CAPACITOR, FIXED, MICA DIELECTRIC: 360 uuf, ±2%, 500 vdc; Erie #370FA (For authorized allowances see Group III)			1					C1010
	P1	F		5910-667-5666	/	/	/				CAPACITOR, FIXED, MICA DIELECTRIC: 600 uuf, ±2%, 500 vdc; Erie type 370FA			1	1.0	0.5	3.0		C1011
	P1	F		5910-284-4026	/	/	/				CAPACITOR, FIXED, MICA DIELECTRIC: 720 uuf, ±2%, 500 vdc; Erie #370FA (Item No. C1005 thru 1008, C1012 thru 1016)			9	2.0	1.3	27.0		See Desc column
	P1	F		5910-666-8450	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 330,000 uuf, ±10%, 300 vdc; Sprague #186P33493S13			1	1.0	0.5	3.0		C1001
	P1	F		5910-668-4913	/	/	/				CAPACITOR, VARIABLE, AIR DIELECTRIC: 22.5 uuf min, 405 uuf max; Sig dwg #SM-D-143650-3			2	1.0	0.5	6.0		C1002, 1003
	M	D			/	/	/				CLAMP, LOOP: 5/8 in lg x 9/32 in w x 1/4 in h; Sig dwg #SM-B-143736			1					
	M	D			/	/	/				CLAMP, LOOP: 11/16 in lg x 9/32 in w x 5/16 in h; Sig dwg #SM-B-143309			1					
	P1	F		5975-396-3116	/	/	/				CLAMP, LOOP: .656 in lg x 5/8 in w x .200 in thk; Sig dwg #SM-B-144451 (Authorized allowances based on a total of 9 per equip)			2	1.5	1.0	9		H1005, 1006
	M	D			/	/	/				CLIP, ELECTRICAL: 5/32 in lg x .211 in w x .176 in h; Sig dwg #SM-143423			1					
	P1	F		5820-780-2602	/	/	/				CLUTCH, FRICTION: Sig dwg #SM-B-143703			1	1.0	0.5	2.0		
	P1	F		5935-259-6798	/	/	/				CONNECTOR, RECEPTACLE, ELECTRICAL: 11 cont; Sig dwg #SM-C-283191			1	1.0	0.5	2.0		P1001
	P1	F		5305-754-4308	/	/	/				CONTACT, ELECTRICAL: 9/32 in lg x 1/4 in across flats; 6-32 NC-2A x 3/16 in; Sig dwg #SM-B-143666			1	1.0	0.5	2.0		S1001

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
																		FIGURE NO.	ITEM NO.
A	B	C	D																
											T-195/GRC-19 (continued)								
	P1	F		5820-571-1829	/	/	/				CONTACT, ELECTRICAL: 2-1/8 in lg x 21/32 in w x 11/16 in d; Sig dwg #SM-B-143728			1	1.0	0.5	2.0		J1001
	P1	F		5930-204-6826	/	/	/				CONTACT, ASSEMBLY, ELECTRICAL: c/o limit sw; 1.218 in lg x 19/32 in w x 1-5/8 in h; Auto Mfg #SW45-1779			1	1.0	0.5	2.0		S1003
	M	D			/	/	/				COVER, ELECTRICAL: 3-1/16 in lg x 1-3/4 in w x 9/16 in h; Sig dwg #SM-B-143656			1					
	M	D			/	/	/				GEAR, ASSEMBLY: Sig dwg #SM-B-143711			1					
	P1	F		5820-780-2603	/	/	/				GEAR, ASSEMBLY: c/o 2 gears; Sig dwg #SM-B-143690			1	1.0	0.5	2.0		01006
	P1	F		5820-780-2604	/	/	/				GEAR, ASSEMBLY: c/o 2 gears; Sig dwg #SM-B-143695			1	1.0	0.5	2.0		01007
	P1	F		5820-785-5147	/	/	/				GEAR, SPUR: 17 teeth, .5312 in dia x .245 in thk; Sig dwg #SM-B-143687			1	1.0	0.5	1.0		H1004
	P1	F		5820-808-9539	/	/	/				GEAR, SPUR: 23 teeth, .78125 in dia x .176 in w; Sig dwg #SM-B-143644			1	1.0	0.5	1.0		
	P1	F		5820-808-9540	/	/	/				GEAR, SPUR: 60 teeth, 1.29166 in dia x .281 in w; Sig dwg #SM-B-143663			2	1.0	0.5	2.0		
	M	D			/	/	/				INSERT, ELECTRICAL: Sig dwg #SM-B-356710			2					
		F		6615-322-5365	/	/	/				MOTOR, CONTROL: 400 cyc, 115 v, .260 amp, 1030 ohm; Kearfoot #R-110-2B-C (For authorized allowances see Group III)			1					B1001
	M	D			/	/	/				PLATE, ELECTRICAL: 1-1/16 in lg x 3/4 in w x 5/32 in h; Sig dwg #SM-B-143731			2					
	M	D			/	/	/				PLATE, ELECTRICAL: 1-1/16 in lg x 3/16 in w x .218 in h; Sig dwg #SM-B-143730			1					
	M	D			/	/	/				PLATE, ELECTRICAL SHIELD: 1-1/8 in lg x 3/8 in w x .091 in thk; Sig dwg #SM-B-143673			1					
	M	D			/	/	/				PLATE, ELECTRICAL SHIELD: 1.781 in lg x 1.740 in w x .093 in thk; Sig dwg #SM-B-143675			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				PLATE, ELECTRICAL SHIELD: 2-5/8 in lg x 1-1/8 in w x 3/32 in thk; Sig dwg #SM-B-143679			1					
	M	D			/	/	/				PLATE, ELECTRICAL SHIELD: 3-1/4 in lg x 2-1/2 in w x .187 in thk; Sig dwg #SM-C-143681			1					
	M	D			/	/	/				PLATE, ELECTRICAL SHIELD: 4.031 in lg x 2-1/2 in w x .187 in thk; Sig dwg #SM-B-143701			1					
	M	D			/	/	/				PLATE, ELECTRICAL SHIELD: 3.843 in lg x 1.761 in w x .187 in thk; Sig dwg #SM-B-143716			1					
	P1	F		5935-259-6624	/	/	/				PLUG, TIP: 21/32 in lg o/a; EF Johnson #108-790-5			1	1.0	0.5	2.0		P1002
	M	D			/	/	/				POST, BINDING: .625 in lg x 3/8 in dia; Sig dwg #SM-B-143486			1					
	M	D			/	/	/				POST, BINDING: .125 in lg x .156 in dia; Sig dwg #SM-B-143562			1					
	M	D			/	/	/				RACK ASSEMBLY: Sig dwg #SM-C-357201			1					
	M	D			/	/	/				RETAINER, CAPACITOR: 3-22/32 in lg x 1 in w x 21/32 in h; Sig dwg #SM-B-143725			1					
	M	D			/	/	/				RETAINER, CAPACITOR: 3-23/32 in lg x 1 in w x 31/32 in h; Sig dwg #SM-B-143726			1					
	P1	F		5340-877-6090	/	/	/				RETAINER, CAPACITOR: Sig dwg #SM-B-143686			1	1.0	0.5	1.0		
	P1	F		5340-286-9473	/	/	/				RING, RETAINER: .112 in ID x .010 in thk; Waldes pt #5100-12			2	1.0	0.5	2.0		H1002
	P1	F		5340-697-1728	/	/	/				RING, RETAINING: .094 in ID x .015 in thk; Waldes #5133-12C			1	1.0	0.5	1.0		H1007
	M	D			/	/	/				ROLLER, ARM: 1/4 in dia x .156 in lg; Sig dwg #SM-B-143670			1					
	M	D			/	/	/				SHAFT, SHOULDER: 7/32 in dia x .265 in lg; Sig dwg #SM-B-143671			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				SHAFT, SHOULDER: 1.781 in lg x 1.870 in dia; Sig dwg #SM-B-143708			1					
	M	D			/	/	/				SHIM: Sig dwg #SM-B-356709			1					
	M	D			/	/	/				SPACER, SLEEVE: .169 in dia x .160 in lg; Sig dwg #SM-B-143672			1					
	M	D			/	/	/				SPACER, SLEEVE: 1/4 in dia x .125 in lg; Sig dwg #SM-B-143290-2			1					
	M	D			/	/	/				SPACER, SLEEVE: 1/4 in dia x .125 in lg; Sig dwg #SM-B-143662			4					
	P1	F		5910-598-4954	/	/	/				SPRING, HELICAL, EXTENSION: 1.030 in lg o/a x 7/32 in dia; Sig dwg #SM-B-143658			1	1.0	0.5	2.0		01003
	P1	F		5820-571-1827	/	/	/				SWITCH, SUBASSY LINEAR: 4-1/8 in lg x 2-1/2 in w x 1 in h; Sig dwg #SM-D-357203			1	1.0	0.5	4.0		S1002
	M	D			/	/	/				TERMINAL BOARD: Sig dwg #SM-C-357202			1					
	M	D			/	/	/				WASHER, FLAT: 3/16 in ID x 11/32 in OD x .015 in thk; Sig dwg #SM-B-143704			1					
	M	D			/	/	/				WASHER, FLAT: 3/16 in ID x 11/32 in OD x .005 in thk; Sig dwg #SM-B-143705			6					
	M	D			/	/	/				WASHER, FLAT: .093 in ID x 1/4 in OD x .025 in thk; MIL Std MS-15795-302			2					
	M	D			/	/	/				WASHER, FLAT: 1/8 in ID x 5/16 in OD x .040 in thk; MIL Std MS-15795			2					
	M	D			/	/	/				WASHER, FLAT: 1/8 in ID x 5/16 in OD x .027 in thk; Sig dwg #SM-D-143650-12			3					
	M	D			/	/	/				WASHER, FLAT: No. 6; Sig dwg #SM-D-143650-7			2					
	M	D			/	/	/				WASHER, FLAT: .130 in ID x 1/4 in OD x .005 in thk; Sig dwg #SM-D-143651			5					
	M	D			/	/	/				WIRING ASSEMBLY: Sig dwg #SM-D-143734			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued) GROUP V DYNAMOTOR, HIGH VOLTAGE NOTE: When Dynamotor HV is no longer operational or feasible for repair it should be replaced by transistorized power supply (FSN 5820-962-5383).								
	P1	F		5977-284-6757	/						BRUSH, ELECTRICAL CONTACT: high voltage, set of 2 ea; replacement for Collins pt/ dwg 231-0485-00; Collins pt/dwg 540-5493-001			1	1.0	0.5	2.0		
	P1	F		5977-284-6570	/						BRUSH, ELECTRICAL CONTACT: high voltage, set of 2, replacement for Collins pt/dwg 231-0068-00; Collins pt/dwg 234-0451-00			1	1.0	0.5	2.0		
	P1	F		5977-284-6723	/						BRUSH, ELECTRICAL CONTACT: low voltage, set of 2; Electrolux type 3008-41; Collins pt #234-0450-00			1	1.0	0.5	2.0		
	P1	F		5977-284-6728	/						BRUSH, ELECTRICAL CONTACT: low voltage, set of 2, replacement for Collins pt #231-0485-00; Collins #540-9194-001			1	1.0	0.5	2.0		
	P1	F		5977-552-7214	/						CAP, ELECTRICAL: plastic, 25/64 in lg x 7/8 in dia; Collins pt #234-0909-00			2	1.0	0.5	2.0		
											GROUP VI DYNAMOTOR, LOW VOLTAGE NOTE: When Dynamotor LV is no longer operational or feasible for repair it should be replaced by Transistorized Power Supply (FSN 5820-962-5382).								
	P1	F		5977-284-6569	/	/					BRUSH, ELECTRICAL CONTACT: Collins pt #231-0414-00			1	1.0	0.5	2.0		
	P1	F		5977-284-6727	/	/					BRUSH, ELECTRICAL CONTACT: Collins pt #234-0407-00			2	1.0	0.5	2.0		
	P1	F		5977-284-6750	/	/					BRUSH, ELECTRICAL CONTACT: Sig dwg SC-D-105906-1; Collins #234-0408-00			1	1.0	0.5	2.0		
	P1	F		5910-100-8057	/	/					CAPACITOR, FIXED, MICA DIELECTRIC: 3000 uuf, ±5%, 500 vdc; MIL #CM-30B302J			1	1.0	0.5	3.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-667-4962	/	/					CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 400 vdc; Collins #231-0446-00			1	1.0	0.5	3.0		
	P1	F		5910-567-2628	/	/					CAPACITOR, FIXED, PAPER DIELECTRIC: 22,000 uuf, ±20%, 100 vdc; Sprague #75P22301			1	1.0	0.5	3.0		
	P1	F		5977-542-9848	/	/					CAP, ELECTRICAL: plastic, 13/64 in lg x 1/2 in dia; Redmond #29A25			1	1.0	0.5	2.0		
	P1	F		5977-257-7057	/	/					CAP, ELECTRICAL: bakelite, .281 in lg x 3/4 in dia; Redmond #29A26			2	1.0	0.5	2.0		
	P1	F		5905-537-6716	/	/					RESISTOR, ADJUSTABLE: 40 ohm, ±10%, -0%, 5 w; Collins #234-0419-00			1	1.0	0.5	2.0		
	P1	F		5905-270-5736	/	/					RESISTOR, FIXED, W/W: 75 ohm, ±10%, 5 w; Collins #234-0420-00			1	1.0	0.5	2.0		
	P1	F		5977-545-7674	/	/					SPRING, HELICAL, TORSION: 8rd coils, .120 in lg x .1918 in OD x .160 in ID; Collins #234-0406-00			6	1.0	0.7	6.0		
											GROUP VII MODULATOR SUBASSEMBLY								
	P1	H	R	5820-691-2045	/	/	/				MODULATOR, SUBASSEMBLY: 4-1/4 in lg x 2-7/8 in w; Sig dwg SM-D-143744		NX	1		0.5	2.0		
	M	D			/	/	/				BRACKET, ANGLE: 4-3/16 in lg x 1-1/16 in w x 9/16 in h; Sig dwg SM-C-143785			1					
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-D-143791			1					
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-D-143792			1					
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-D-143804			1					
	P1	F		5820-396-3213	/	/	/				CAP, ELECTRICAL: for relay K403; Sig dwg SM-C-143399 (For authorized allowances see Group II)			1					
	P1	F		5910-195-6589	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 12 uuf, ±10%, 500 vdc; MIL #CC20CH120K			1	1.0	0.5	3.0		C407
	P1	F		5910-183-9214	/	/	/				CAPACITOR, FIXED, MICA DIELECTRIC: 1200 uuf, ±10%, 2500 vdc; MIL #CM45B122K			1	1.0	0.5	3.0		C415

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-666-7394	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 100 vdc; Sprague #86P10301S5			1	1.0	0.5	3.0		C404
	P1	F		5910-668-6149	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 100 vdc; Sprague #196P10301S4 (For authorized allowances see Group II)			2					C403,417
	P1	F		5910-667-5383	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 300 vdc; Sprague #96P10303S4 (For authorized allowances see Group II)			1					C420
	P1	F		5910-666-8459	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 68,000 uuf, ±20%, 300 vdc; Sprague #96P68303S2			3	1.3	0.7	9.0		C401,408, 410
	P1	F		5910-666-8276	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 100,000 uuf, ±20%, 100 vdc; Sprague #P66898			2	1.0	0.5	6.0		C421,427
	P1	F		5910-667-5366	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 330,000 uuf, ±20%, 300 vdc; Sprague #86P33403S5			1	1.0	0.5	3.0		C409
	P1	F		5910-649-3962	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 330,000 uuf, ±20%, 300 vdc; Sprague #96P33403T16			2	1.0	0.5	6.0		C411,412
	P1	F		5910-666-8322	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 1 uf, ±20%, 300 vdc; Sprague #86P10503S5			1	1.0	0.5	3.0		C405
	P11	F		5910-643-6892	/	/	/				CAPACITOR, FIXED, ELECTROLYTIC: 4 uf, 60 vdc; Fan Steel #PP4B60A2 (For authorized allowances see Group III)			1					C406
	P1	F		5910-668-4615	/	/	/				CAPACITOR, FIXED, ELECTROLYTIC: 4 uf, 60 vdc; Fan Steel #PP4B60A1			1	1.0	0.5	3.0		C424
	P1	F		5910-666-6989	/	/	/				CAPACITOR, FIXED, ELECTROLYTIC: 50 uf, 50 vdc; GE pt #29F444 (authorized allowances based on a total of 3 per equip)			2	1.0	0.5	6.0		C402,423
	M	D			/	/	/				CHASSIS ASSEMBLY: modulator; Sig dwg SM-D-143781			1					
	M	D			/	/	/				CHASSIS ASSEMBLY: modulator; Sig dwg SM-D-143784			1					
	M	D			/	/	/				CHASSIS ASSEMBLY: modulator; Sig dwg SM-D-143794			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				CHASSIS: modulator, 8-1/2 in lg x 6-3/8 in w x 2-5/8 in h; Sig dwg SM-D-143789			1					
	M	D			/	/	/				CHASSIS: modulator, 4-9/32 in lg x 2-15/16 in w x 7/8 in h; Sig dwg SM-D-143801			1					
	M	D			/	/	/				CLAMP, CABLE: 13/16 in lg x 9/32 in w x 7/16 in h; Sig dwg SM-B-143755			1					
	M	D			/	/	/				CLAMP, CABLE: 1-1/16 in lg x 3/8 in w x .560 in h; Sig dwg SM-B-143756			1					
	M	D			/	/	/				CLIP, ELECTRICAL: 5/32 in lg x .172 in w x .195 in h; Sig dwg SM-B-143423			1					
	P1	F		5935-173-5908	/	/	/				CONNECTOR, RECEPTACLE, ELECTRICAL: 20 rd cont; Sig dwg SM-B-283188 (Authorized allowances based on a total of 2 per equip)			1	1.0	0.5	6.0		P401
	P1	O		5960-264-3001	/	/	/				ELECTRON TUBE: MIL #4X150D (For authorized allowances see Group III)			2					V406,407
	P1	O		5960-262-0167	/	/	/				ELECTRON TUBE: MIL #12AT7WA			2	6.6	3.4	200.0		V401,403
	P1	O		5960-262-0185	/	/	/				ELECTRON TUBE: MIL #5726/6AL5W			1	6.6	3.3	100.0		V402
	P1	O		5960-262-0210	/	/	/				ELECTRON TUBE: MIL #5814A			1	3.3	1.7	100.0		
	P1	F		5915-504-8064	/	/	/				FILTER, LOW PASS: 50,000 ohm input imp., 50,000 ohm output imp.; Sig dwg SM-C-143764			1	1.0	0.5	2.0		Z402
	P1	F		5915-504-8065	/	/	/				FILTER, HIGH PASS: 600 ohm input, 10,000 ohm output; Sig dwg SM-C-143765			1	1.0	0.5	2.0		Z401
	P1	F		5970-784-9392	/	/	/				INSULATOR: 1-7/8 in OD x 21/32 in ID x 1/2 in h; Sig dwg SM-C-143761			1	1.0	0.5	2.0		E407
	P1	F		5970-784-9393	/	/	/				INSULATOR: 1-7/8 in OD x 21/32 in ID x 1/2 in h; Sig dwg SM-C-143763			1	1.0	0.5	2.0		E408

SOURCE CODE A	B	C	D	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION FIGURE NO.	ILLUSTRATION ITEM NO.
						T-195/GRC-19 (continued)								
	M	D			/ / /	POST, BINDING: 5/8 in lg x 3/8 in dia; Sig dwg SM-B-143782			4					
	M	D			/ / /	POST, BINDING: 1.796 in lg x 3/8 in dia; Sig dwg SM-B-143783			3					
	M	D			/ / /	POST, BINDING: 5/8 in lg x 3/8 in dia; Sig dwg SM-B-143802			3					
	M	D			/ / /	POST, BINDING: 1 in lg x 3/16 in sq; Sig dwg SM-B-143778			2					
	M	D			/ / /	POST, BINDING: 2-1/32 in lg x 3/16 in hex; Sig dwg SM-B-143757			2					
	M	D			/ / /	POST, BINDING: 7/8 in lg x 3/16 in hex; Sig dwg SM-B-143758			2					
	M	D			/ / /	POST, BINDING: .922 in lg x .433 in hex; Sig dwg SM-B-143397-3			1					
		F		5935-201-8579	/ / /	PLUG, TIP: std phone tip cont. element; 7/8 in lg o/a; Sig dwg SM-B-143534 (For authorized allowances see Group III)			1					P402
		F		5935-500-5039	/ / /	PLUG, TIP: med phone tip cont. element; 7/8 in lg o/a; Sig dwg SM-B-143535 (For authorized allowances see Group III)			1					P403
	P1	F		5945-808-9756	/ / /	RELAY ARMATURE: cont arrangement 1A, 1B; 250 vdc, .010 amp; Sig dwg SM-D-143768-1			1	1.0	0.5	3.0		K402
	P1	O		5945-259-6610	/ / /	RELAY THERMAL: spst, ac, dc, 27.5 v max, 6 amp nom; Sig dwg SM-C-143751			1	1.0	0.5	3.0		K403
	M	D			/ / /	RESISTOR ASSEMBLY: Sig dwg SM-C-143776			1					
	P1	F		5905-252-1952	/ / /	RESISTOR, FIXED, COMPOSITION: 10 ohm, ±5%, 2 w; MIL #RC42GF100J			1	1.0	0.5	3.0		R412
	P1	F		5905-195-6449	/ / /	RESISTOR, FIXED, COMPOSITION: 24 ohm, ±5%, 2 w; MIL #RC42GF240J			1	1.0	0.5	3.0		R449
	P1	F		5905-253-1217	/ / /	RESISTOR, FIXED, COMPOSITION: 82 ohm, ±10%, 2 w; MIL RC42GF820K			2	1.0	0.5	6.0		R433,434

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5905-279-2643	/	/	/				RESISTOR, FIXED, COMPOSITION: 100 ohm, ±5%, 1 w; MIL #RC32GF100J (For authorized allowances see Group III)			1					R402
	P1	F		5905-186-3008	/	/	/				RESISTOR, FIXED, COMPOSITION: 100 ohm, ±10%, 1/2 w; MIL #RC20GF101K (Authorized allowances based on a total of 4)			1	1.0	0.7	9.0		R453
	P1	F		5905-171-1975	/	/	/				RESISTOR, FIXED, COMPOSITION: 150 ohm, ±5%, 2 w; MIL RC43GF150J			2	1.0	0.5	6.0		R401,432
	P1	F		5905-192-3971	/	/	/				RESISTOR, FIXED, COMPOSITION: 330 ohm, ±5%, 1/2 w; MIL RC20GF331J			1	1.0	0.5	3.0		R437
	P1	F		5905-284-3745	/	/	/				RESISTOR, FIXED, W/W: 400 ohm, ±5%, 8 w; MIL RW30G401 (For authorized allowances see Group III)			1					R417
	P1	F		5905-171-2005	/	/	/				RESISTOR, FIXED, COMPOSITION: 470 ohm, ±10%, 1/2 w; MIL RC20GF471K (Authorized allowances based on a total of 2)			1	1.0	0.5	6.0		R424
	P1	F		5905-279-2555	/	/	/				RESISTOR, FIXED, COMPOSITION: 910 ohm, ±5%, 1 w; MIL RC32GF911J			1	1.0	0.5	3.0		R420
	P1	F		5905-195-6806	/	/	/				RESISTOR, FIXED, COMPOSITION: 1000 ohm, ±5%, 1/2 w; MIL RC20GF102J			1	1.0	0.5	3.0		R403
	P1	F		5905-258-0087	/	/	/				RESISTOR, FIXED, FILM: 2085 ohm, ±1%, 1/2 w; Concarbon #NA-15			1	1.0	0.5	3.0		R441
	P1	F		5905-185-8516	/	/	/				RESISTOR, FIXED, COMPOSITION: 10,000 ohm, ±10%, 1/2 w; MIL RC20GF103K (Authorized allowances based on a total of 4 per equip)			2	1.0	0.5	6.0		R404,410
	P1	F		5905-299-2029	/	/	/				RESISTOR, FIXED, COMPOSITION: 10,000 ohm, ±10%, 1 w; MIL RC32GF103K (Authorized allowances based on a total of 3)			1	1.0	0.7	9.0		R421
	P1	F		5905-190-8876	/	/	/				RESISTOR, FIXED, COMPOSITION: 15,000 ohm, ±10%, 1/2 w; MIL RC20GF153K			2	1.0	0.5	6.0		R430,431
	P1	F		5905-249-4227	/	/	/				RESISTOR, FIXED, COMPOSITION: 18,000 ohm, ±10%, 2 w; MIL RC42GF183K			2	1.0	0.7	9.0		R428,429

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
P1 F	5905-249-4243	/ / /	RESISTOR, FIXED, COMPOSITION: 27,000 ohm, ±10%, 2 w; MIL RC42GF273K			1	1.0	0.5	3.0		R409
P1 F	5905-249-4248	/ / /	RESISTOR, FIXED, COMPOSITION: 33,000 ohm, ±10%, 1/2 w; MIL RC20GF333K (Authorized allowances based on a total of 2)			1	1.0	0.5	6.0		R427
P1 F	5905-295-3410	/ / /	RESISTOR, FIXED, COMPOSITION: 47,000 ohm, ±10%, 1/2 w; MIL RC20GF473K (For authorized allowances see Group III)			2					R406,408
P1 F	5905-279-6761	/ / /	RESISTOR, FIXED, COMPOSITION: 51,000 ohm, ±5%, 1/2 w; MIL RC20GF513J			1	1.0	0.5	3.0		R418
P1 F	5905-195-6761	/ / /	RESISTOR, FIXED, COMPOSITION: 100,000 ohm, ±5%, 1/2 w; MIL RC20GF104J (For authorized allowances see Group II)			1					R423
P1 F	5905-195-6500	/ / /	RESISTOR, FIXED, COMPOSITION: 120,000 ohm, ±10%, 1/2 w; MIL RC20GF124K (Authorized allowances based on a total of 4)			3	1.0	0.8	12.0		R407,415, 422
P1 F	5905-192-0662	/ / /	RESISTOR, FIXED, COMPOSITION: 180,000 ohm, ±10%, 1/2 w; MIL RC20GF184K			1	1.0	0.5	3.0		R416
P1 F	5905-295-3409	/ / /	RESISTOR, FIXED, COMPOSITION: 220,000 ohm, ±10%, 1/2 w; MIL RC20GF224K (For authorized allowances see Group II)			3					R411,426, 452
P1 F	5905-295-3012	/ / /	RESISTOR, FIXED, FILM: 470,000 ohm, ±10%, 1 w; IRC type DCF			2	1.0	0.5	6.0		R439,446
P1 F	5905-192-3982	/ / /	RESISTOR, FIXED, COMPOSITION: 1 meg, ±10%, 1/2 w; MIL RC20GF105K (For authorized allowances see Group II)			1					R405
P1 F	5905-279-1961	/ / /	RESISTOR, FIXED, COMPOSITION: 1.3 meg, ±5%, 2 w; MIL RC42GF135J			1	1.0	0.5	3.0		R425
P1 F	5905-279-1874	/ / /	RESISTOR, FIXED, COMPOSITION: 1.8 meg, ±10%, 1/2 w; MIL RC20GF185K			1	1.0	0.8	3.0		R413
P1 F	5905-279-1882	/ / /	RESISTOR, FIXED, COMPOSITION: 2.7 meg, ±10%, 1/2 w; MIL RC20GF275K			1	1.0	0.5	3.0		R448

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	Pl	F		5905-819-9874	/	/	/				RESISTOR, VARIABLE: 250,000 ohm, ±20%, 1 w; MIL RV2LAXSA254B			1	1.0	0.5	3.0		R414
	Pl	F		5905-843-8053	/	/	/				RESISTOR, VARIABLE: 500,000 ohm, ±20%, 1 w; MIL RV2LAXSA504B			1	1.0	0.5	3.0		R436
	Pl	F		5905-843-8054	/	/	/				RESISTOR, VARIABLE: 1 meg, ±20%, 1 w			1					R419
	M	D			/	/	/				SHIELD, ELECTRICAL: Sig dwg SM-D-143789-2			1					
	Pl	O		5960-296-4175	/	/	/				SHIELD, ELECTRON TUBE: 1-3/8 in lg x 0.930 in dia; Sig dwg SM-C-143429-1			1	1.0	0.5	2.0		E402
	Pl	O		5960-636-0115	/	/	/				SHIELD, ELECTRON TUBE: 1-15/16 in lg x .950 in dia x 1.065 in d; Sig dwg SM-C-143429-5 (For authorized allowances see Group II)			3					E401,403, 404
	Pl	F		5935-502-4721	/	/	/				SOCKET, ELECTRON TUBE: 7 miniature cont; MIL TS102P02 (For authorized allowances see Group II)			1					XK403
	Pl	F		5935-260-0516	/	/	/				SOCKET, ELECTRON TUBE: 7 miniature cont; MIL TS102P01 (For authorized allowances see Group II)			1					XV402
	Pl	F		5935-160-1365							SOCKET, ELECTRON TUBE: 9 cont; noval size; MIL TS103P01 (For authorized allowances see Group II)			3					XV401, 403, 404
	Pl	F		5935-696-4735							SOCKET, ELECTRON TUBE: 8 pin, 5 cont missing; Eitel-M-Culloug #Y-101 (For authorized allowances see Group III)			2					XV406, 407
	M	D			/	/	/				SPACER, SLEEVE: 1/4 in lg x .156 in dia; Sig dwg SM-B-143773			1					
	M	D			/	/	/				STIFFENER: 4-1/16 in lg x 3/8 in wd x .964 in thk; Sig dwg SM-B-143786			1					
	M	D			/	/	/				STIFFENER: 1-1/4 in lg x 9/16 in wd x 15/16 in h; Sig dwg SM-B-143787			1					
	M	D			/	/	/				STIFFENER: 3-1/4 in lg x 3/8 in wd x 5/8 in h; Sig dwg SM-B-143788			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL							DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D																FIGURE NO.	ITEM NO.
												T-195/GRC-19 (continued)								
	M	D			/	/	/					STRAP, RETAINING: 15/16 in lg x 3/8 in wd x .014 in thk; Sig dwg SM-B-143772			1					
	M	D			/	/	/					STRAP, RETAINING: 3/4 in lg x 5/16 in w x 3/8 in h; Sig dwg SM-C-143759			6					
	M	D			/	/	/					TERMINAL BOARD ASSEMBLY: Sig dwg SM-C-143769			1					
	M	D			/	/	/					TERMINAL BOARD: 3-5/8 in lg x 1-13/16 in w x 3/32 in h; Sig dwg SM-B-143775			1					
	M	D			/	/	/					TERMINAL BOARD: 2-3/4 in lg x 1-5/8 in w x 3/32 in thk; Sig dwg SM-C-143780			1					
	P1	F		5950-506-1531	/	/	/					TRANSFORMER, AF: modulation type, 250 ohm max pri, 175 ohm max secd; ct; Sig dwg SM-D-143767			1	1.0	0.5	3.0		T402
	P1	F		5950-648-1514	/	/	/					TRANSFORMER, AF: pri wnd 1080 ohm, 8 madc secd 650 ohm; Sig dwg SM-D-143766			1	1.0	0.5	3.0		T401
	M	D			/	/	/					WIRING ASSEMBLY: Sig dwg SM-E-143790			1					
												GROUP VIII OSCILLATOR, RADIO FREQUENCY EXCITER ASSEMBLY								
	P1	H	R	5820-503-1196	/	/	/					OSCILLATOR, R.F.: exciter assy; freq 1.5 to 20 mc .1 band; master osc freq control; Sig dwg SM-D-143286		NX	1		0.3	3.0		
	M	D			/	/	/					BAR, HOLDING: 2.187 in lg x 3/8 in w x 5/16 in h; Sig dwg SM-B-143297			1					
	M	D			/	/	/					BEARING, SLEEVE: 11/64 in lg x 15/32 in dia; Sig dwg SM-C-283156-1			3					
	M	D			/	/	/					CAM: irregular shape; 1-1/2 in lg x .062 in thk; Sig dwg SM-B-143315			1					0-114
	M	D			/	/	/					CABLE ASSEMBLY: Sig dwg SM-D-143369			1					
	M	D			/	/	/					CAM: irregular shape, 1-1/2 in lg x .062 in thk; Sig dwg SM-B-143318			1					0-115

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
P1 F	5910-543-0823	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 2 uuf, ±0.25 uuf, 500 vdc; MIL CC20CK020C			3	1.0	0.7	9.0		C120,130, 131
P1 F	5910-192-2245	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 3 uuf, ±0.25 uuf, 500 vdc; MIL CC20CJ030D			1	1.0	0.5	3.0		C109
P1 F	5910-228-5944	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 4 uuf, ±1/2 uuf; 500 vdc; MIL CC20CH040D			1	1.0	0.5	3.0		C124
P1 F	5910-174-9242	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 7 uuf, ±0.5 uuf; 500 vdc; MIL CC20CH070D (For authorized allowances see Group III)			1					C113
P1 F	5910-577-1049		CAPACITOR, FIXED, CERAMIC DIELECTRIC: 1.2 uuf, ±2%, 500 vdc; MIL CC20UJ120G			2	1.0	0.5	6.0		C116,117
P1 F	5910-280-5132	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 15 uuf, ±5%, 500 vdc; MIL CC30CH150J			2	1.0	0.5	6.0		C114,125
P1 F	5910-666-8058	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 18 uuf, ±5%, 500 vdc; MIL CC20UJ180J			1	1.0	0.5	3.0		C105
P1 F	5910-537-5208	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 22 uuf, ±5%, 500 vdc; MIL CC20UJ220J			1	1.0	0.5	3.0		C121
P1 F	5910-577-6812	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 30 uuf, ±2%, 500 vdc; MIL CC21TH300G			1	1.0	0.5	3.0		C119
P1 F	5910-666-8865		CAPACITOR, FIXED, MICA DIELECTRIC: 56 uuf, ±5%, 500 vdc; Electro Motive #605			2	1.0	0.5	6.0		C108,110
P1 F	5910-643-9268	/ / /	CAPACITOR, FIXED, MICA DIELECTRIC: 120 uuf, ±5%, 500 vdc; Electro Motive #605			1	1.0	0.5	3.0		C137
P1 F	5910-235-2221	/ / /	CAPACITOR, FIXED, MICA DIELECTRIC: 150 uuf, ±5%, 500 vdc; Electro Motive #605			1	1.0	0.5	3.0		C132
P1 F	5910-666-7658	/ / /	CAPACITOR, FIXED, CERAMIC DIELECTRIC: 220 uuf, ±5%, 500 vdc; Centralab #DA316			1	1.0	0.5	3.0		C142
P1 F	5910-538-3242	/ / /	CAPACITOR, FIXED, MICA DIELECTRIC: 3.30 uuf, ±5%, 300 vdc; MIL CM15D331J			1	1.0	0.5	3.0		C123
P1 F	5910-280-7185	/ / /	CAPACITOR, FIXED, MICA DIELECTRIC: 510 uuf, ±5%, 300 vdc; MIL CM15D511J			1	1.0	0.5	3.0		C112

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-667-5329	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 1000 uuf, ±20%, 600 vdc; Sprague #96P1020684			1	1.0	0.5	3.0		C106
	P1	F		5910-265-3295	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±10%, 200 vdc; Sprague #75P10392 (For authorized allowances see Group III)			3					C101,102, 103
	P1	F		5910-667-5192	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 400 vdc; Sprague #86P10304310 (Item No. C104, 115, 126, 128, 134, 135)			6	1.0	1.1	18.0		See Desc column
	P1	F		5910-242-7654	/	/	/				CAPACITOR, FIXED, PAPER DIELECTRIC: 10,000 uuf, ±20%, 400 vdc; Sprague #91P10304			1	1.0	0.5	3.0		C143
	P1	F		5910-809-8929	/	/	/				CAPACITOR, FIXED, ELECTROLYTIC: 20 uf, 300 vdc; Sprague #D16523			1	1.0	0.5	3.0		C146
	P1	F		5910-197-6715	/	/	/				CAPACITOR, VARIABLE, CERAMIC: 5 to 12 uuf, 350 vdc; Sig dwg SM-B-91278 (Authorized allowances based on a total of 5)			4	1.5	0.9	15.0		C122,129, 131,134
	P1	F		5910-666-7980	/	/	/				CAPACITOR, VARIABLE, CERAMIC: 5 to 30 uuf, 350 vdc; Erie #557-02 (Item No. C107, 111, 118, 136, 138, 140)			6	2.1	1.0	18.0		See Desc
	M	D			/	/	/				CHASSIS, OSC: 7.406 in lg x 3-3/4 in w x 1-17/32 in h; Sig dwg SM-C-143364			1					
	M	D			/	/	/				CLAMP, CAPACITOR: 1-3/8 in lg x 1-3/8 in w x 3/4 in h; Sig dwg SM-C-143307			1					
	M	D			/	/	/				CLAMP, CABLE: 3/4 in lg x 5/16 in w x 3/8 in h; Sig dwg SM-B-143795			1					
		F		5975-396-3116	/	/	/				CLAMP, LOOP: Sig dwg SM-B-144451 (For authorized allowances see Group IV)			2					H104
	M	D			/	/	/				CLIP, ELECTRICAL: 1 in lg x 3/8 in w x 1/4 in h; Sig dwg SM-B-143368			1					
		F		5950-393-1467	/	/	/				COIL, RF: 2.2 mh at 350 kc; 4 pie universal wnd; Sig dwg SM-C-143376-18 (For authorized allowances see Group III)			1					L112

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5950-393-1477	/	/	/				COIL, RF: 43 uh; 1 pie universal wnd; Sig dwg SM-B-143374			1	1.0	0.5	3.0		L111
	P1	F		5950-301-4494	/	/	/				COIL, RF: single layer wnd; 49.5 turns, No. 26 AWG; Sig dwg SM-C-143335			2	1.0	0.5	6.0		Z101,102
	P1	F		5950-537-5119	/	/	/				COIL, RF: 1 wnd, 35.5 turns No. 30 AWG; Sig dwg SM-C-143348			1	1.0	0.5	3.0		Z103
	P1	F		5950-314-2071	/	/	/				COIL, RF: 1 wnd; 19 turns, No. 20 AWG; Sig dwg SM-C-143350			1	1.0	0.5	3.0		Z105
	P1	F		5950-532-3715	/	/	/				COIL, RF: 1 wnd, 6 to 12 mc; Sig dwg SM-C-143353			1	1.0	0.5	3.0		Z104
	P1	F		5950-537-5122	/	/	/				COIL, RF: 49.5 turns; 1 wnd; Sig dwg SM-C-143354			1	1.0	0.5	3.0		Z108
	P1	F		5950-314-2072	/	/	/				COIL, RF: 1 wnd; 67.5 turns; Sig dwg SM-C-143355			1	1.0	0.5	3.0		Z107
	P1	F		5950-314-2073	/	/	/				COIL, RF: 1 wnd; 26 turns; Sig dwg SM-C-143358			1	1.0	0.5	3.0		Z109
	P1	F		5950-314-2074	/	/	/				COIL, RF: 1 wnd, 13.5 turns; Sig dwg SM-C-143360			1	1.0	0.5	3.0		Z110
	P1	F		5950-393-1476	/	/	/				COIL, RF: 1 wnd, 19 turns; Sig dwg SM-C-143363			1	1.0	0.5	3.0		Z106
	P1	F		5935-295-5006	/	/	/				CONNECTOR, RECEPTACLE: 15 rd male cont; Sig dwg SM-C-283194 (For authorized allowances see Group II)			1					P101
	P1	F		5935-244-5728	/	/	/				CONNECTOR, RECEPTACLE: 1 female cont; Sig dwg SM-B-41673			1	1.0	0.5	6.0		J101
	P1	F		5950-648-1336	/	/	/				CORE, ADJUSTABLE TUNING: 2-13/64 in lg x 1/4 in dia; Sig dwg SM-C-143330 (p/o Z109 thru 110)			10	1.0	1.4	20.0		
	P1	F		5820-780-2591	/	/	/				COUPLING, SHAFT, RIGID: 1 in dia x 11/32 in thk; Sig dwg SM-B-143393			1	1.0	0.5	2.0		0-108
	P1	F		5820-780-2593	/	/	/				COUPLING, SHAFT, RIGID: 1 in dia x 3/8 in thk; Sig dwg SM-B-143394			1	1.0	0.5	1.0		0-109

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
P1 O	5960-262-0152	/ / /	ELECTRON TUBE: MIL 6AU6WA			1	3.3	1.7	100.0		V101
P1 O	5960-188-3551	/ / /	ELECTRON TUBE: MIL 6AK6			2	32.8	16.4	200.0		V102,103
P1 O	5960-188-3915	/ / /	ELECTRON TUBE: MIL 5763 (For authorized allowances see Group III)			1					V104
M D		/ / /	FERRULE, ELECTRICAL CONDUCTOR: 1/2 in dia x 15 in lg; Sig dwg SM-B-170621			4					
M D		/ / /	FOLLOWER: .249 in dia x .248 in lg; Sig dwg SM-B-143303			2					
M D		/ / /	PLATE, ASSEMBLY: 4.230 in lg x 3-3/4 in w x .125 in thk; Sig dwg SM-B-143319			1					
M D		/ / /	PLATE ASSEMBLY: 3-3/4 in lg x 3.187 in w x .125 in thk; Sig dwg SM-B-143323			1					
M D		/ / /	PLATE ASSEMBLY: 1 in lg x 7/16 in w x 1/4 in thk; Sig dwg SM-B-143328			10					
M D		/ / /	PLATE, ELECTRICAL, SHIELD: 1-3/4 in sq x .064 in thk; Sig dwg SM-B-143300			1					
M D		/ / /	RACK: 7.35 in lg x 1-15/16 in w x 2-23/64 in h; Sig dwg SM-B-143325			1					
P1 F	5905-279-1732	/ / /	RESISTOR, FIXED, COMPOSITION: 56 ohm, ±10%, 1 w; MIL RC32GF560K			1	1.0	0.5	3.0		R122
P1 F	5905-665-5276	/ / /	RESISTOR, FIXED, W/W: 64 ohm, ±3%, 2 w; Dale Prod. #RS-2			1	1.0	0.5	3.0		R123
P1 F	5905-186-3008	/ / /	RESISTOR, FIXED, COMPOSITION: 100 ohm, ±10%, 1/2 w; MIL RC20GF101K (For authorized allowances see Group VII)			1					R102
P1 F	5905-100-4814	/ / /	RESISTOR, FIXED, W/W: 160 ohm, ±5%, 8 w; MIL RW30G161			1	1.0	0.5	3.0		R121
P1 F	5905-195-6817	/ / /	RESISTOR, FIXED, COMPOSITION: 1000 ohm, ±10%, 1/2 w; MIL RC20GF102K (For authorized allowances see Group II)			1					R120

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5905-279-2672	/	/	/				RESISTOR, FIXED, COMPOSITION: 1800 ohm, ±10%, 1/2 w; MIL RC20GF182K (For authorized allowances see Group II)			1					R116
	P1	F		5905-279-1720	/	/	/				RESISTOR, FIXED, COMPOSITION: 2700 ohm, ±10%, 1 w; MIL RC32GF272K			1	1.0	0.5	3.0		R118
	P1	F		5905-195-6449	/	/	/				RESISTOR, FIXED, COMPOSITION: 4700 ohm, ±10%, 2 w; MIL RC42GF472K			2	1.0	0.5	6.0		R107,111
	P1	F		5905-245-0023	/	/	/				RESISTOR, FIXED, COMPOSITION: 6800 ohm, ±10%, 1/2 w; MIL RC20GF682K (Authorized allowances based on a total of 3)			2	1.0	0.7	9.0		R106,110
	P1	F		5905-185-8516	/	/	/				RESISTOR, FIXED, COMPOSITION: 10,000 ohm, ±10%, 1/2 w; MIL RC20GF103K (For authorized allowances see Group VII)			2					R101,115
	P1	F		5905-299-2029	/	/	/				RESISTOR, FIXED, COMPOSITION: 10,000 ohm, ±10%, 1 w; MIL RC32GF103K (For authorized allowances see Group VII)			1					R105
	P1	F		5905-190-8879	/	/	/				RESISTOR, FIXED, COMPOSITION: 18,000 ohm, ±10%, 1/2 w; MIL RC20GF183K (Authorized allowances based on a total of 2 per equip)			1	*	0.5	3.0		R114
	P1	F		5905-299-2023	/	/	/				RESISTOR, FIXED, COMPOSITION: 18,000 ohm, ±5%, 1 w; MIL RC32GF183J			1	1.0	0.5	3.0		R117
	P1	F		5905-120-0487	/	/	/				RESISTOR, FIXED, COMPOSITION: 33,000 ohm, ±10%, 1 w; MIL RC32GF333K (For authorized allowances see Group III)			1					R103
	P1	F		5905-192-9260	/	/	/				RESISTOR, FIXED, COMPOSITION: 150,000 ohm, ±10%, 1/2 w; MIL RC20GF154K (For authorized allowances see Group II)			1					R119
	P1	F		5340-256-2461	/	/	/				RING, RETAINING: Waldes #5100-31-C			18	1.5	1.0	18.0		
	P1	F		5340-619-3376	/	/	/				RING, RETAINING: .095 in ID x .016 in thk; Waldes #5133-12-S (Authorized allowances based on a total of 7)			2	1.5	0.9	5.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5340-263-5875	/	/	/				RING, RETAINING: .154 in ID x .025 in thk; Waldes #5133-18-G			5	2.0	1.1	14.0		
	M	D			/	/	/				ROD, STRAIGHT, HEADLESS: 7.562 in lg x .219 in dia; Sig dwg SM-B-143292			3					
	P	F		5305-754-3173	/	/	/				SCREW, CAPTIVE, SOCKETHEAD: Sig dwg SM-D-143286			2					
	P1	F		5935-592-8265	/	/	/				SHELL, ELECTRICAL CONNECTOR: Sig dwg SM-B-143370			1	1.0	0.5	2.0		
	P1	0		5960-564-4772	/	/	/				SHIELD, ELECTRON TUBE: Sig dwg SM-C-143429-2 (Authorized allowances based on a total of 5 per equip)			3	1.0	0.5	6.0		E101,102, 103
	P1	0		5960-284-4352	/	/	/				SHIELD, ELECTRON TUBE: Sig dwg SM-C-143429-6 (For authorized allowances see Group III)			1					E104
	P1	F		5935-260-0516	/	/	/				SOCKET, ELECTRON TUBE: MIL #TS102P01 (For authorized allowances see Group)			3					XV102, 102,103
	P1	F		5935-160-1365	/	/	/				SOCKET, ELECTRON TUBE: MIL #TS103P01			1					XV104
	P1	F		5340-200-7899	/	/	/				SPRING, HELICAL, EXTENSION: 1-7/16 in lg o/a x 3/16 in OD; Sig dwg SM-B-143289			2	1.0	0.5	4.0		0-110, 111
	M	D			/	/	/				STUD, CONTINUOUS THREAD: 8/32 NC2A x 1/2 in lg; Sig dwg SM-B-143332			1					
	M	D			/	/	/				SUPPORT: aluminum, 1-5/16 in lg x 5/16 in w x 1/4 in h; Sig dwg SM-B-143293			1					
	M	D			/	/	/				SUPPORT: aluminum, 2-1/8 in lg x .312 in w x .218 in h; Sig dwg SM-B-143294			1					
	M	D			/	/	/				SUPPORT: aluminum, 2-1/4 in lg x .656 in w x 3/8 in h; Sig dwg SM-B-143299			1					
	P1	F		5930-395-9389	/	/	/				SWITCH SECTION ASSEMBLY, ROTARY: 63 cct, 3 dummy clips; 10 moving and 51 fixed non-pile up cont; Sig dwg SM-D-143288			1	1.0	0.5	3.0		S101A thru E
	M	D			/	/	/				TERMINAL BOARD: plastic; 1-31/32 in lg x 1-3/8 in w x 3/32 in thk; Sig dwg SM-B-143372			1					

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
M D		/ / /	TERMINAL BOARD: 7-1/2 in lg x 1-1/2 in w x 3/32 in thk; Sig dwg SM-B-143377			1					
M D		/ / /	WASHER, FLAT: .191 in ID x 3/8 in OD x .018 in thk; Sig dwg SM-B-143291			2					
M D		/ / /	WASHER, FLAT: 1/8 in ID x .244 in OD x .025 in thk; Sig dwg SM-B-143296			24					
M D		/ / /	WIRING ASSEMBLY: Sig dwg SM-E-143367			1					

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
			GROUP IX OSCILLATOR, RADIO FREQUENCY (VFO)								
P1 H R	5820-503-1140	/ / /	OSCILLATOR, RADIO FREQUENCY: (vfo) 1.5 to 3 mc; 1 band; Sig dwg SM-C-143980		NX	1		0.5	3.0		
P1 F	5910-195-7572	/ / /	CAPACITOR, FIXED, CERAMIC: 100 uuf, ±5%, 500 vdc; MIL CC30UJ101J			1	1.0	0.5	3.0		C809
P1 F	5910-235-2223	/ / /	CAPACITOR, FIXED, MICA: 200 uuf, ±2%; Electro Motive #605			1	1.0	0.5	3.0		C807
P1 F	5910-666-7228	/ / /	CAPACITOR, FIXED, CERAMIC: 1000 uuf, ±20%, 500 vdc; Centralab #BC			1	1.0	0.5	3.0		C811
P1 F	5910-668-5918	/ / /	CAPACITOR, FIXED, CERAMIC: 5000 uuf, ±20%, 500 vdc; Aerovex #BPD			1	1.0	0.5	3.0		C812
P1 F	5910-284-5212	/ / /	CAPACITOR, FIXED, PAPER: 10,000 uuf, ±20%, 300 vdc; Sprague #86P10303S1			2	1.0	0.5	6.0		C808,810
P1 F	5910-667-5383		CAPACITOR, FIXED, PAPER: 10,000 uuf, ±10%, 300 vdc; Sprague #96P10303S4 (For authorized allowances see Group II)			1					C806
P1 F	5950-395-9256	/ / /	COIL, RF: 100 uh at 2.5 mc; 25 ma dc, 150 turns single nylon E copper wire; Collins #240-0099-00			1	1.0	0.5	3.0		L802
P1 F	5935-201-8462	/ / /	CONNECTOR, PLUG: 1 male coax cont; Amphenol #82-830 (Authorized allowances based on a total of 2)			1	1.0	0.5	4.0		P801
P1 F	5935-636-5913	/ / /	CONNECTOR, RECEPTACLE: 7 rd male cont; Sig dwg SM-C-283198 (Authorized allowances based on a total of 2)			1	1.0	0.5	4.0		P802
P1 F	5935-521-0574	/ / /	COVER, ELECTRICAL, CONNECTOR: 1-11/32 in lg x 23/32 in dia; Sig dwg SM-B-283197 (p/o P802) (Authorized allowances based on a total of 2)			1	1.0	0.5	4.0		
P1 O	5960-264-2089	/ / /	ELECTRON TUBE: MIL 5749/6BA6W			2	4.4	2.2	200.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5820-019-7948	/	/	/				GEAR ASSEMBLY: Sig dwg SM-B-144225			1	1.0	0.5	1.0		
	P1	F		5905-299-2029	/	/	/				RESISTOR, FIXED, COMPOSITION: 10,000 ohm, ±10%, lw; MIL RC32GF103K (For authorized allowances see Group VII)			1					R806
	P1	F		5905-299-2025	/	/	/				RESISTOR, FIXED, COMPOSITION: 15,000 ohm, ±10%, 1 w; MIL RC32GF153K			1	1.0	0.5	3.0		R803
	P1	F		5905-249-4248	/	/	/				RESISTOR, FIXED, COMPOSITION: 33,000 ohm, ±10%, 1/2 w; MIL RC32GF333K (For authorized allowances see Group VII)			1					R805
	P1	F		5905-192-3988	/	/	/				RESISTOR, FIXED, COMPOSITION: 56,000 ohm, ±10%, 1/2 w; MIL RC20GF563K (For authorized allowances see Group II)			1					R804
	P1	F		5905-249-3661	/	/	/				RESISTOR, FIXED, COMPOSITION: 68,000 ohm, ±5%, 1/2 w; MIL RC20GF683J			2	1.0	0.5	6.0		R801,802
	P1	0		5960-564-4772	/	/	/				SHIELD, ELECTRON TUBE: Sig dwg SM-C-143429-2 (For authorized allowances see Group VIII)			2					E801,802
	P1	F		5935-260-0516	/	/	/				SOCKET, ELECTRON TUBE: 7 miniature cont; MIL TS102p01 (For authorized allowances see Group II)			2					XV802
	P1	F		5930-573-1909	/	/	/				SWITCH, THERMOSTATIC: spst; Collins #292-0036-00			1	1.0	0.5	5.0		S801
											GROUP X PANEL AND FRAME ASSEMBLY								
	M	D									ACTUATOR ASSEMBLY: Sig dwg SM-B-144305			1					
	M	D									ACTUATOR: Sig dwg SM-B-144306			1					
	P1	F		6625-569-0243	/	/	/				AMMETER: 0 to 500 cw graduated in 100 sealed 1 v; 1-27/32 in sq x 23/64 in thk; Sig dwg SM-C-144326			1	1.0	0.5	2.0		M602
	P1	F		5905-537-4070	/	/	/				ATTENUATOR, VARIABLE: Sig dwg SM-B-144325			1	1.0	0.5	3.0		R602
	P1	F		5820-396-3093	/	/	/				BAR, LOCKING: c/o locking screw w/knob; Collins #505-7699-002			2	1.0	0.5	2.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				BASE: 3-1/16 in lg x 9/16 in w x 1.031 in h; Sig dwg SM-C-144138			1					
	P1	F		5930-636-2683	/	/	/				BLADE, ELECTRICAL SWITCH: 2-3/8 in lg x 5/8 in w x 13/32 in thk; Sig dwg SM-C-144387			1	1.0	0.5	2.0		S613
	M	D			/	/	/				BLOCK: 11/16 in lg x 0.375 in w x 0.419 in thk; Sig dwg SM-B-144351			6					
	P1	F		5820-019-7949			/				BLOWER ASSEMBLY, EXHAUST: Sig dwg SM-D-357530		NX	1	1.0	0.5	1.0		
	M	D			/	/	/				BRACKET: Sig dwg SM-B-144062			1					
	M	D			/	/	/				BRACKET: Sig dwg SM-B-144338			1					
	M	D			/	/	/				BRACKET: Sig dwg SM-C-144090			1					
	P1	F		5977-284-6573	/	/	/				BRUSH, ELECTRICAL CONTACT: set of 2, replacement part for B60.2; Collins #230-0196-00, dwg #540-5195-001			1	1.0	0.5	2.0		
	P1	F		5977-284-9435	/	/					BRUSH, ELECTRICAL CONTACT: set of 2, replacement part for B602; Collins #230-0194-00, dwg #234-0214-00			1	1.0	0.5	2.0		
	P1	F		5977-284-9987	/	/	/				BRUSH, ELECTRICAL CONTACT: set of 2; replacement part for B603; Collins #230-0211-00 and 230-0212-00; Revere Camera #1700-9-2			2	1.0	0.5	4.0		
	P1	F		5977-284-9988	/	/	/				BRUSH, ELECTRICAL CONTACT: set of 2; replacement for B601; Collins #230-0155-00 and 230-0218-00; dwg #231-0355-00			2	1.0	0.5	4.0		
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-B-144105			1					
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-B-144405			1					
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-C-144250			1					
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-D-144398			1					
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-D-144399			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				CABLE ASSEMBLY: Sig dwg SM-E-144107			1					
	P1	F		5977-201-4445	/	/	/				CAP, ELECTRICAL: used with 230-0155-00 and 230-0218-00; Collins #234-0354-00			2	1.0	0.5	4.0		
	P1	F		5977-279-6438	/	/					CAP, ELECTRICAL: Collins #234-0243-00			1	1.0	0.5	2.0		
	P1	F		5977-502-6808	/	/					CAP, ELECTRICAL: Collins #234-0421-00			2	1.0	0.5	4.0		
	P1	O		5940-566-3862	/	/	/				CAP, ELECTRICAL: rubber; cover for binding post J615; Lorraine Mfg #1010			1	1.0	0.5	2.0		E627
	P	O		5920-523-1940	/	/	/				CAP, ELECTRICAL: cap for fuseholder; Littelfuse #342006-5A1			1	1.0	0.5	3.0		
	M	D			/	/	/				CAPACITOR ASSEMBLY: Sig dwg SM-B-144120			1					
	M	D			/	/	/				CAPACITOR ASSEMBLY: Sig dwg SM-C-144410			1					
	P1	F		5910-889-4338	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 15 uuf, ±5%, 5000 vdc; Centralab #DA 853-15Z			1	1.0	0.5	3.0		C655
	P1	F		5910-667-6175	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 25 uuf, ±10%, 5000 vdc; Centralab #DA853-017			1	1.0	0.5	3.0		C663
	P1	F		5910-667-6126	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 40 uuf, ±5%, 5000 vdc; Centralab #DA853-019			3	1.0	0.7	9.0		C653,654, 656
	P1	F		5910-667-6180	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 40 uuf, ±10%, 15,000 vdc; Centralab #DA857-013 (Item No. C649 thru 652, 661, 662)			6	2.0	1.0	18.0		See Desc column
	P1	F		5910-667-6120	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 50 uuf, ±10%, 15,000 vdc; Centralab #DA857-014			3	1.2	0.7	9.0		C647,648, 660
	P1	F		5910-667-5668	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 400 uuf, ±20%, 500 vdc; Sangamo #M74			1	1.0	0.5	3.0		C657
	P1	F		5910-667-6081	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 1000 uuf, 500 vdc; Centralab #DA906-011M (Item No. C605 thru 620, C624 thru 631, C635 thru 640, C664, 665)			32	5.0	3.1	96.0		See Desc column
	P1	F		5910-101-4726	/	/	/				CAPACITOR, FIXED, MICA: 4700 uuf, ±10%, 2500 vdc; MIL CM50B472K			1	1.0	0.5	3.0		C623

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL							DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D																FIGURE NO.	ITEM NO.
												T-195/GRC-19 (continued)								
	P1	F		5910-265-3295	/	/	/					CAPACITOR, FIXED, PAPER: 10,000 uuf, ±10%, 300 vdc; Sprague #75P10392 (For authorized allowances see Group III)			1					C623
	P1	F		5910-553-3501	/	/	/					CAPACITOR, FIXED, CERAMIC DIELECTRIC: 10,000 uuf, ±20%, 75 vdc; Glen Co. #MIN-M-01-M			3	1.2	0.7	9.0		C667,668, 669
	P1	F		5910-519-9809			/					CAPACITOR, FIXED, CERAMIC DIELECTRIC: 20,000 uuf, ±20%, 500 vdc; Glen Co. #CBM-02-8			1	1.0	0.5	3.0		C666
	P1	F		5910-669-1683	/	/	/					CAPACITOR, FIXED, PAPER: 68,000 uuf, ±20%, 200 vdc; Sprague #86P6830251			1	1.0	0.5	3.0		C602
	P1	F		5910-649-1725	/	/	/					CAPACITOR, FIXED, PAPER: 100,000 uuf, ±20%, 100 vdc; Sprague #196P10401S4			4	1.5	0.8	12.0		C621,644, 645,658
	P1	F		5910-270-5343	/	/	/					CAPACITOR, FIXED, PAPER: 100,000 uuf, ±20%, 100 vdc; Sprague #86P10401S1 (For authorized allowances see Group III)			5					
	P1	F		5910-668-3624	/	/	/					CAPACITOR, FIXED, PAPER: 200,000 uuf, ±20%, 1500 vdc; Sig dwg SM-D-143971-10			1	1.0	0.5	3.0		C659
	P1	F		5910-666-8351	/	/	/					CAPACITOR, FIXED, PAPER: 680,000 uuf, ±20%, 100 vdc; Sprague #96P68401S2			1	1.0	0.5	3.0		C601
	P1	F		5910-879-3576	/	/	/					CAPACITOR, FIXED: Sprague #112D307C7030P1			1	1.0	0.5	3.0		
	P1	F		5910-686-9894			/					CAPACITOR, FIXED, PAPER: 4 uf, ±10%, 200 vdc; Sprague #118P4059252			1	1.0	0.5	3.0		C671
	P1	F		5910-668-5985	/	/	/					CAPACITOR, FIXED, ELECTROLYTIC: 10 uf, 50 vdc; GE #29F494			1	1.0	0.5	3.0		C642
	P1	F		5910-666-6989								CAPACITOR, FIXED, ELECTROLYTIC: 50 uf, 50 vdc; GE #29F444 (For authorized allowances see Group VII)			1					C643
	M	D			/	/	/					CHASSIS ASSEMBLY: Sig dwg SM-B-144102			1					
	M	D			/	/	/					CHASSIS ASSEMBLY: Sig dwg SM-C-144100			1					
	M	D			/	/	/					CHASSIS: Sig dwg SM-C-144103			1					

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
										FIGURE NO.	ITEM NO.
A B C D											
			T-195/GRC-19 (continued)								
P1 F	5950-537-5061	/ / /	CHOKE, RF: 640 ma dc max based on 1/2 w each ±25° C, 400 ma max each 85° C; Jeffers Elect #10203-34			2	1.0	0.5	6.0		L602,610
P1 F	5950-546-6623	/ / /	CHOKE, RF: 5 mc freq; 2-3/8 in lg x 1 in dia x 1-7/37 in h; National Coil #C-0047136			2	1.0	0.5	6.0		L601,622
M D		/ / /	CLAMP: Sig dwg SM-C-357266			1					
M D		/ / /	CLAMP: Sig dwg SM-C-357267			1					
P1 F	5940-170-1700	/ / /	CLIP, ELECTRICAL: 9/16 in h x 13/32 in lg x 0.385 in w; Littelfuse #1217			8	2.0	1.2	8.0		
M D		/ / /	CLUTCH ASSEMBLY: Sig dwg SM-C-144295			1					0-603
P1 F	5950-250-8733	/ / /	COIL, RF: 1-5/32 in lg x 5/8 in dia; Sig dwg SM-D-144123-10			1	1.0	0.3	2.0		L614
P1 F	5950-784-0783	/ / /	COIL, SOLENOID: Sig dwg SM-C-144007-2			1	1.0	0.5	2.0		K614B
M D		/ / /	COLLAR: Sig dwg SM-C-144298			1					
P1 F	5935-201-8410	/ / /	CONNECTOR, RECEPTACLE: 1-1/2 in lg x 11/32 in w x 1-5/32 in h o/a; Sig dwg SM-C-144113			2	1.0	0.5	6.0		J618,619
M D		/ / /	CONNECTOR ASSEMBLY: Sig dwg SM-B-144186			2					
M D		/ / /	CONNECTOR ASSEMBLY: Sig dwg SM-B-144189			1					
M D		/ / /	CONNECTOR ASSEMBLY: Sig dwg SM-B-144191			1					
P1 F	5935-201-5210	/ / /	CONNECTOR, PLUG: 21/32 in lg x 1-7/8 in dia excluding term; Amphenol #164-102-20S			1	1.0	0.5	3.0		J601
P1 F	5935-189-6245	/ / /	CONNECTOR, RECEPTACLE: 1-1/2 in lg x 3/4 in w x 7/16 in h o/a; Amphenol #126-150			3	1.0	0.7	9.0		
P1 F	5935-201-3998	/ / /	CONNECTOR, RECEPTACLE: 1-3/16 in lg x 1-15/32 in dia; MIL C-12S20A type CS2020(1) (P)			1	1.0	0.5	3.0		J605

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
										FIGURE NO.	ITEM NO.
A B C D			T-195/GRC-19 (continued)								
P1 F	5935-201-7043	/ / /	CONNECTOR, RECEPTACLE: 1-3/16 in lg x 7/8 in dia; Amphenol #82-811			1	1.0	0.5	3.0		J614
P1 F	5935-201-8462	/ / /	CONNECTOR, RECEPTACLE: 1 male coax cont; Amphenol #82-830 (For authorized allowances see Group IX)			1					J601
P1 F	5935-258-4653	/ / /	CONNECTOR, RECEPTACLE: 1-3/16 in lg x 1-15/32 in dia o/a; MIL C-12520A type CS2020 (2) (S)			1	1.0	0.5	3.0		J604
P1 F	5935-258-8170	/ / /	CONNECTOR, RECEPTACLE: 1-1/32 in lg x 9/16 in dia; Amphenol 26-192; Sig dwg SM-B-283200			2	1.0	0.5	4.0		J609
P1 F	5935-258-8572	/ / /	CONNECTOR, RECEPTACLE: 1-15/16 in lg x 3/4 in w x 13/32 in h o/a; Amphenol #926-807; Sig dwg SM-C-283189			2	1.0	0.5	4.0		J606,612
P1 F	5935-259-1087	/ / /	CONNECTOR, RECEPTACLE: 19/16 in lg x 0.570 in dia o/a; MIL UG-657/U			3	1.1	0.7	6.0		J602,613, 613
P1 F	5935-259-3318	/ / /	CONNECTOR, RECEPTACLE: 1-11/16 in lg x 3/4 in w x 0.415 in h; Amphenol #26-805; Sig dwg SM-C-283192			1	1.0	0.5	2.0		J610
P1 F	5935-549-2646	/ / /	CONNECTOR, RECEPTACLE: 1-1/16 in lg x 1-9/32 in dia o/a; MIL C10544U-79/U			1	1.0	0.5	2.0		J603
P1 F	5820-571-1826	/ / /	CONTACT, INTERUNIT: 1.118 in dia x 9/32 in thk o/a; Sig dwg SM-B-144087			1	1.0	0.5	2.0		E606
P1 F	5820-587-3625	/ / /	CONTACT, INTERUNIT: Sig dwg SM-B-144087-1			1	1.0	0.5	2.0		E605
P1 H	6680-503-1489	/ / /	COUNTER, ROTATING, FIXED MOUNTING: numbered 1 to 10; 1-17/32 in x 3-39/64 in o/a; Veeder-Root #A148600			1		1.0	2.0		M601
P1 O	5820-039-7257	/ / /	COVER, AIR OUTLET: 2-1/8 in lg x 2 in w x 1-9/16 in thk; Sig dwg SM-C-144218			1	1.0	0.5	2.0		
P1 O	5820-096-7084	/ / /	COVER, AIR OUTLET: 7-3/8 in lg x 2-15/32 in w x 9/16 in thk; Sig dwg SM-C-144207			1	1.0	0.5	2.0		
P1 F	5935-258-1767	/ / /	COVER, ELECTRICAL CONNECTOR: 23/32 in lg x 9/16 in h; Jeens #CW123A/W			1	1.0	0.5	2.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5935-539-0735	/	/	/				COVER, ELECTRICAL CONNECTOR: 5/8 in lg x 1-3/4 in dia o/a; Amphenol #164-447			1	1.0	0.5	2.0		
	M	D			/	/	/				COVER: Sig dwg SM-B-144039			1					
	M	D			/	/	/				COVER: Sig dwg SM-B-144441			1					
	M	D			/	/	/				COVER: Sig dwg SM-B-144442			1					
	P1	O		5935-502-9672	/	/	/				COVER, ELECTRICAL CONNECTOR: Sig dwg SM-C-140971-3			1	1.0	0.5	3.0		
	P1	F		5920-650-6562	/	/	/				COVER, ASSEMBLY: (apply correct decal) Sig dwg SM-B-144445			1	1.0	0.5	2.0		
	M	D			/	/	/				DIAL: 2.625 in ID x 0.093 in thk o/a; Sig dwg SM-C-143999			1					
	M	D			/	/	/				DUCT: 2 in OD x 0.187 in thk o/a; Sig dwg SM-B-144133			1					0-647
	P1	O		5960-503-4880	/	/	/				ELECTRON TUBE: MIL OA2WA			1	6.6	3.3	100		V601
	P1	O		4130-262-7143	/	/	/				FILTER, AIR CONDITIONING: 6-27/36 in lg x 1-63/64 in w x 1-3/32 in h; Sig dwg SM-C-143971-18			1	1.0	0.5	2.0		
	P1	F		5330-729-4604	/	/	/				FELT, MECHANICAL PREFORMED: Sig dwg SM-B-144061			3	1.0	0.7	3.0		
	M	D			/	/	/				FRAME ASSEMBLY: Sig dwg SM-D-144029			1					
	M	D			/	/	/				FRAME ASSEMBLY: Sig dwg SM-B-144046			1					
	M	D			/	/	/				FRAME ASSEMBLY: Sig dwg SM-D-144098			1					
	M	D			/	/	/				FRAME ASSEMBLY: Sig dwg SM-D-144123			1					
	M	D			/	/	/				FRAME ASSEMBLY: Sig dwg SM-C-144197			1					
	M	D			/	/	/				FRAME ASSEMBLY: Sig dwg SM-D-144047			1					
	M	D			/	/	/				FRAME: Sig dwg SM-D-144099			1					
	M	D			/	/	/				FRAME: Sig dwg SM-D-144198			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	O		5920-142-4824	/	/	/				FUSE, CARTRIDGE: 10 amp 32 volt; MIL #F05A10ROB			1	1.0	0.5	5.0		F602
	P1	O		5920-012-0151	/	/	/				FUSE, CARTRIDGE: 15 amp 32 volt; MIL #F04A15ROB			1	1.0	0.5	5.0		F601
	P1	O		5920-565-0035	/	/	/				FUSE, CARTRIDGE: 30 amp, 32 volt; MIL #F05A30ROB			1	1.0	0.5	5.0		F603
	P1	F		5920-553-4420	/	/	/				FUSEHOLDER: 2-1/8 in lg x 15/16 in dia o/a; Littelfuse 342006			1	1.0	0.5	3.0		XF601
	P1	F		5820-562-6292	/	/	/				GASKET, RUBBER: 0.115 in dia aperture 6-31/32 in x 2-3/32 in w o/a; Sig dwg SM-C-143988			1	1.0	0.5	2.0		
	P1	F		5820-562-6293	/	/	/				GASKET, RUBBER: 0.115 dia aperture 19/32 in lg x 19/32 in w; Sig dwg SM-B-143989			2	1.0	0.5	4.0		
	P1	F		5820-692-6484	/	/	/				GASKET, RUBBER: 21-15/16 in lg x 10-47/64 in w x 0.120 in thk; Sig dwg SM-C-143283			1	1.0	0.5	2.0		
	P1	F		9320-561-0973	/	/	/				GASKET, BULK: 0.406 in w x 0.187 in h x 0.093 in thk o/a; Atlantic India Rubber #2131 (Authorized allowances will be a minimum of or a multiple of 1 ft)	Ft		1-1/2	1.0	0.5	2.0		
	P1	F		5820-696-4757	/	/	/				GASKET: 1.234 in ID x 0.139 in w; Aeronautical Standards #AN6227B23 (Air Force & Navy)			2	1.0	0.5	4.0		
	P1	F		5820-780-2594	/	/	/				GASKET: 3-1/8 in lg x 2-5/8 in w o/a; Sig dwg SM-B-144342			1	1.0	0.5	2.0		
	M	D			/	/	/				GASKET ASSEMBLY: Sig dwg SM-B-144437			1					
	M	D			/	/	/				GASKET ASSEMBLY: Sig dwg SM-B-144158			1					
	P1	H		5820-738-2484	/	/	/				GEAR, SPUR: Sig dwg SM-C-144059			1		0.5	2.0		
	M	D			/	/	/				GEAR, SPUR: Sig dwg SM-C-144296			4					
	P1	H		5820-060-7438	/	/	/				GEAR, SPUR: 16 teeth, 1 w/auto tone; Sig dwg SM-B-179016			1		0.5	2.0		
	P1	F		5325-558-4493	/	/	/				GROMMET, RUBBER: 3/8 in OD x 3/16 in h o/a; Veeder -Root #V510951			2	1.0	0.5	4.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	Pl	F		5820-780-2595	/	/	/				GRIP: brass; Sig dwg SM-B-144464			1	1.0	0.5	2.0		
	Pl	F		5977-521-8749	/	/					HOLDER, BRUSH: for motor B602; Continental #C-44683			1	1.0	0.5	2.0		
	Pl	F		5977-340-2112	/	/					HOLDER, BRUSH: for motor B602; Continental #C-44682			1	1.0	0.5	2.0		
	Pl	F		5977-296-6611	/	/	/				HOLDER, ELECTRICAL CONTACT BRUSH: for motor B602; Hamilton Beach #AUC-37			2	1.0	0.5	4.0		
	M	D			/	/	/				HOUSING ASSEMBLY, BLOWER: Sig dwg SM-C-357264			1					
	M	D			/	/	/				HOUSING ASSEMBLY, BLOWER: Sig dwg SM-C-357265			1					
	M	D			/	/	/				HOUSING ASSEMBLY, BLOWER: Sig dwg SM-C-357277			1					
	M	D			/	/	/				HUB ASSEMBLY: Sig dwg SM-B-144302			1					
	M	D			/	/	/				HUB ASSEMBLY: Sig dwg SM-C-144303			1					
	Pl	F		4140-894-0538	/	/	/				IMPELLER, CENTRIFUGAL, FAN: Sig dwg SM-D-357530-2			1	1.0	0.5	2.0		
	Pl	F		4140-851-4507	/	/	/				IMPELLER, CENTRIFUGAL FAN: Sig dwg SM-D-357530-5			1	1.0	0.5	2.0		
	M	D			/	/	/				INSULATOR ASSEMBLY: Sig dwg SM-B-144431			1					
	M	D			/	/	/				INSULATOR: Sig dwg SM-B-144019			1					
	M	D			/	/	/				INSULATOR: Sig dwg SM-B-144024			1					
	Pl	F		5970-680-9699	/	/	/				INSULATOR PLATE: 3.124 in lg x 2.624 in w x 0.437 in h; Sig dwg SM-C-144344			1	1.0	0.5	2.0		
	M	D			/	/	/				INSULATOR PLATE: Sig dwg SM-B-143993			1					
	M	D			/	/	/				INSULATOR PLATE: Sig dwg SM-B-143994			1					
	M	D			/	/	/				INSULATOR PLATE: Sig dwg SM-B-144432			1					
	M	D			/	/	/				INSULATOR STANDOFF: Sig dwg SM-B-144042			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	O		5355-163-9955	/	/	/				KNOB: Sig dwg SC-B-16552			4	1.0	0.8	12.0		
	P1	O		5355-170-4537	/	/	/				KNOB: Electromatic #502501; Sig dwg SM-B-144319			1	1.0	0.5	3.0		
	P1	O		5355-667-9004	/	/	/				KNOB: Sig dwg SM-B-143975			1	1.0	0.5	3.0		
	P1	O		5355-721-8952	/	/	/				KNOB: Sig dwg SM-B-144418			1	1.0	0.5	3.0		
	P1	O		5355-855-4385	/	/	/				KNOB: Sig dwg SM-B-144318			1	1.0	0.5	3.0		
	P1	O		5355-577-4084	/	/	/				KNOB: Sig dwg SM-B-144358			1	1.0	0.5	3.0		
	P1	O		5355-842-8704	/	/	/				KNOB: Sig dwg SM-B-144240			2	1.0	0.5	6.0		
	P1	O		6240-155-8714	/	/	/				LAMP, INCANDESCENT: GE #MS25231-313			4	1.0	0.8	12.0		I601, 602 603, 605
	P1	F		6250-592-7732	/	/	/				LAMPHOLDER ASSEMBLY: Veeder-Root #W510952			1	1.0	0.5	3.0		XI-602
	P1	F		6250-299-6658	/	/	/				LAMPHOLDER: 75 w, 125 v; Dial Co. #711			1	1.0	0.5	2.0		XI-602
	P1	H		5325-817-0759	/	/	/				LATCH, SNAPSLIDE FASTENER: Dimco Gray Co. #A10S-1			1		1.0	2.0		
	P1	H		5325-286-7579	/	/	/				LATCHGUIDE, SNAPSLIDE FASTENER: Dimco Gray Co. #A105-2			1		1.0	2.0		
	M	D			/	/	/				LEAD, ASSEMBLY ELECTRICAL: Sig dwg SM-B-144395			1					
	M	D			/	/	/				LEAD, ASSEMBLY ELECTRICAL: Sig dwg SM-B-144396			1					
	M	D			/	/	/				LEAD, ASSEMBLY ELECTRICAL: Sig dwg SM-B-144397			1					
	M	D									LEAD, ASSEMBLY, ELECTRICAL: Sig dwg SM-B-144400			1					
	M	D			/	/	/				LEAD ASSEMBLY, ELECTRICAL: Sig dwg SM-B-144401			1					
	M	D			/	/	/				LEAD ASSEMBLY, ELECTRICAL: Sig dwg SM-B-144402			1					
	P1	F		5995-295-6417	/	/	/				LEAD, ELECTRICAL: Sig dwg SM-B-144152			1	1.0	0.5	2.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				LEAD, ELECTRICAL: Sig dwg SM-B-144154			1					
	P1	F		6210-635-6076	/	/	/				LIGHT, INDICATOR: 1-9/32 in lg x 13/16 in dia; Dial Co. #88411-111			1	1.0	0.5	3.0		XI-605
	P1	F		5820-780-2596	/	/	/				MASK, DIAL: 1.350 in dia x 0.016 in thk; Sig dwg SM-C-144000			2	1.0	0.5	2.0		
	P1	F		6625-669-0769	/	/	/				METER, AUDIO LEVEL: Sig dwg SM-C-283217			1	1.0	0.5	2.0		M603
	M	D			/	/	/				MOUNT ASSEMBLY: Sig dwg SM-B-144215			1					
	P1	F		6105-895-6665		/					MOTOR, AC: Sig dwg SM-D-357315			1	1.0	0.5	1.0		B602
	P1	F		6105-521-8079	/	/					MOTOR, DC: 27.5 v, 4 amp, .110 hp; Sig dwg SM-C-144156			1	1.0	1.0	2.0		B602
	P1	F		6105-548-1515	/	/	/				MOTOR, DC: 27.5, 0.8 amp; 1/100 hp; Revere Camera #R-118-100 Pm-0212			1	1.0	0.5	2.0		B603
	P1	F		6105-669-6221	/	/	/				MOTOR, DC: Sig dwg SM-D-144081			1	1.0	0.5	2.0		B601
	M	D			/	/	/				MOUNT: Sig dwg SM-C-144218			1					
	M	D			/	/	/				OILER ASSEMBLY: Sig dwg SM-B-144060			3					
	M	D			/	/	/				PAD: Sig dwg SM-B-356806			2					
	M	D			/	/	/				PANEL ASSEMBLY: Sig dwg SM-D-144312			1					
	M	D			/	/	/				PANEL ASSEMBLY: Sig dwg SM-D-144413			1					
	M	D			/	/	/				PANEL ASSEMBLY: Sig dwg SM-D-144415			1					
	M	D			/	/	/				PLATE: Sig dwg SM-C-144082			1					
	M	D			/	/	/				PLATE: Sig dwg SM-B-144108			1					
	M	D			/	/	/				PLATE: Sig dwg SM-B-144332			1					
	M	D			/	/	/				PLATE: Sig dwg SM-B-144420			1					
	M	D			/	/	/				PLATE, ESCTCHEON: Sig dwg SM-C-144350			1					
	M	D			/	/	/				PLATE, IDENTIFICATION: Sig dwg SM-B-144472			1					
	M	D			/	/	/				PLATE, INSTRUCTION: Sig dwg SM-B-144331			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
		M	D		/	/	/				PLATE, SIDE: Sig dwg SM-B-356814			1					
		M	D		/	/	/				PLATE, SIDE: Sig dwg SM-C-357275			1					
		M	D		/	/	/				PLATE, SIDE: Sig dwg SM-C-357276			1					
		P1	F	5820-324-8749	/	/	/				PLUG, TIP: 3 in lg x 2-3/4 in w x 1 in h o/a; Sig dwg SM-C-144201			1	1.0	0.5	2.0		E610
		P1	F	5940-272-1508	/	/	/				POST, BINDING: Sig dwg SM-144312-34			1	1.0	0.5	2.0		J615
		P1	F	5821-696-4761	/	/	/				POST, MOUNTING: Sig dwg SM-B-143397-1			1	1.0	0.5	2.0		XS601
		P1	F	5950-645-6700	/	/	/				REACTOR: Sig dwg SM-C-144141			1	1.0	0.5	2.0		L623
		P1	F	5945-259-5891	/	/	/				RELAY, ARMATURE: Sig dwg SM-C-144092			2	1.0	0.5	4.0		K616,617
		P1	F	5945-259-5892	/	/	/				RELAY, ARMATURE: Sig dwg SM-C-144091			2	1.0	0.5	4.0		K604,609
		P1	F	5945-259-5898	/	/	/				RELAY, ARMATURE: dpdt, 2 amp 28 vdc, 115 vac; Sig dwg SM-C-143408 (For authorized allowances see Group II)			1					K601
		P1	F	5945-295-6665	/	/	/				RELAY, ARMATURE: Sig dwg SM-C-144030			2	1.0	0.5	6.0		K602,612
		P1	F	5945-521-7702	/	/	/				RELAY ARMATURE: Sig dwg SM-C-144044			1	1.0	0.5	3.0		K603
		P1	F	5945-539-1812	/	/	/				RELAY ARMATURE: Sig dwg SM-C-144248			1	1.0	0.5	3.0		K605
		P1	F	5945-688-8977	/	/	/				RELAY ARMATURE: 27.5 v, 40 amp; Stewart-Warner #G576079			1	1.5	0.5	3.0		K610
		P1	F	5945-846-8592	/	/	/				RELAY ARMATURE: 27.5 v; Sig dwg SM-C-357236			1	1.0	0.5	3.0		K608
		P1	F	5945-258-3898	/	/	/				RELAY ARMATURE: 30 vdc, 5 amp make, 3 amp break; Sig dwg SM-B-143768-2			1	1.0	0.5	3.0		K613
		P1	F	5945-259-5885	/	/	/				RELAY ARMATURE: RBM LP type #SA			1	1.0	0.5	3.0		K615
		P1	F	5945-259-5877	/	/	/				RELAY SOLENOID: Sig dwg SM-C-144007			1	1.0	0.5	3.0		
		P1	F	5905-258-0077	/	/	/				RESISTOR, FIXED, W/W: 0.3 ohm, ±1%, 1/2 w; Continental Carbon NA-15			1	1.0	0.5	3.0		R613
		P1	F	5905-264-7113	/	/	/				RESISTOR, FIXED, W/W: 2.0 ohm, ±5%, 8 w; MIL RW30G2R0			2	1.0	0.5	6.0		R622,623

SOURCE CODE A	B	C	D	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION FIGURE NO.	ILLUSTRATION ITEM NO.
						T-195/GRC-19 (continued)								
	P1	F		5905-636-8426	/ / /	RESISTOR, FIXED, W/W: 4.7 ohm, ±1%, 1/2 w; Sig Dwg SM-C-144410-7			1	1.0	0.5	3.0		R618
	P1	F		5905-100-4002	/ / /	RESISTOR, FIXED, W/W: 5 ohm, ±5%, 8 w; MIL #RW3G5R0 (Authorized allowances based on a total of 2)			1	1.0	0.5	6.0		R605
	P1	F		5905-686-2784	/ / /	RESISTOR, FIXED, W/W: 5 ohm, ±10%, 5 w; MIL #RW57G5R0			2	1.0	0.5	6.0		R631,634
	P1	F		5905-284-7118	/ / /	RESISTOR, FIXED, W/W: 10 ohm, ±5%, 8 w; MIL RW30G100			1	1.0	0.5	3.0		R616
	P1	F		5905-173-8784	/ / /	RESISTOR, FIXED, W/W: 12 ohm, ±5%, 10 w;			1	1.0	0.5	3.0		R617
	P1	F		5905-542-7825	/ / /	RESISTOR, FIXED, W/W: MIL RW57G501			2	1.0	0.5	6.0		R632,633
	P1	F		5905-157-0881	/ / /	RESISTOR, FIXED, W/W: 40 ohm, ±5%, 8 w; MIL RW30V400			1	1.0	0.5	3.0		R610
	P1	F		5905-665-5277	/ / /	RESISTOR, FIXED, W/W: 53 ohm, ±5%, 10 w; Sig dwg SM-C-144100-4			1	1.0	0.5	3.0		R611
	P1	F		5905-264-7123	/ / /	RESISTOR, FIXED, W/W: 63 ohm, ±5%, 8 w; MIL RW30G630			1	1.0	0.5	3.0		R621
	P1	F		5905-186-3008	/ / /	RESISTOR, FIXED, COMPOSITION: 100 ohm, ±10%, 1/2 w; MIL RC20GF101K (For authorized allowances see Group VII)			1					R612
	P1	F		5905-100-4745	/ / /	RESISTOR, FIXED, W/W: 120 ohm, ±5%, 8 w; MIL RW30G121			1	1.0	0.5	3.0		R619
	P1	F		5905-279-1971	/ / /	RESISTOR, FIXED, COMPOSITION: 120 ohm, ±10% 2 w; MIL RC42GF121K			1	1.0	0.5	3.0		R615
	P1	F		5905-279-1761	/ / /	RESISTOR, FIXED, COMPOSITION: 620 ohm, ±5%, 1/2 w; MIL RC20GF621J			2	1.0	0.5	6.0		R603,604
	P1	F		5905-844-6428	/ / /	RESISTOR, FIXED, W/W: 2400 ohm, ±3%, 1/8 w; MIL #RB09AE24000F			1	1.0	0.5	3.0		R614
	P1	F		5905-295-4085	/ / /	RESISTOR, FIXED, W/W: 3000 ohm, ±5%, 8 w; Ward Leonard #M-30			1	1.0	0.5	3.0		R601
	P1	F		5905-552-2412	/ / /	RESISTOR, FIXED, COMPOSITION: 3600 ohm, ±1%, 1/2 w; Continental Carbon NA-15			1	1.0	0.5	3.0		R607

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5905-245-0023	/	/	/				RESISTOR, FIXED, W/W: 6800 ohm, ±10%, 1/2 w; MIL RC20GF682K (For authorized allowances see Group VIII)			1					R624
	P1	F		5905-190-8879	/	/	/				RESISTOR, FIXED, COMPOSITION: 18,000 ohm, ±10%, 1/2 w; MIL RC20GF183K (For authorized allowances see Group VIII)			1					R627
	P1	F		5905-190-8873	/	/	/				RESISTOR, FIXED, COMPOSITION: 47,000 ohm, ±10%, 2 w; MIL RC42GF473K			1	1.0	0.5	3.0		R626
	P1	F		5905-195-6500	/	/	/				RESISTOR, FIXED, COMPOSITION: 120,000 ohm, ±10%, 1/2 w; MIL RC20GF124K (For authorized allowances see Group VII)			1					R609
	P1	F		5905-185-6946	/	/	/				RESISTOR, FIXED, COMPOSITION: 470,000 ohm, ±10%, 1/2 w; MIL RC20GF474K (For authorized allowances see Group II)			2					R606,608
	P1	F		5905-284-3535	/	/	/				RESISTOR, FIXED, COMPOSITION: 4.7 meg ±10%, 1/2 w; MIL RC20GF475K			1	1.0	0.5	3.0		R620
	M	D			/	/	/				RETAINER: Sig dwg SM-C-144438			1					
	M	D			/	/	/				RING, INLET: Sig dwg SM-B-356805			2					
	P1	F		5960-570-5280	/	/	/				SEMICONDUCTOR DEVICE, DIODE: Transitron #1N347			1	1.0	0.5	3.0		CR601
	P1	F		5960-696-5405	/	/	/				SEMICONDUCTOR DEVICE, DIODE: Bogue Elect #2SJ5			1	1.0	0.5	3.0		CR602
	P1	F		5960-577-6214	/	/	/				SEMICONDUCTOR DEVICE, DIODE: GE #JG-1N538; Sig dwg SM-D-357530-14			2	1.0	0.5	6.0		CR603, 604
	P1	F		5820-885-3522	/	/	/				SHAFT ASSEMBLY: Sig dwg SM-B-144055			1	1.0	0.5	2.0		0-618
	M	D			/	/	/				SHIELD: Sig dwg SM-C-144459			1					
		F		5960-295-7652	/	/	/				SHIELD, ELECTRON TUBE: Sig dwg SM-C-143429-3 (For authorized allowances see Group II)			1					E626
		F		5935-260-0516	/	/	/				SOCKET, ELECTRON TUBE: MIL TS102P01 (For authorized allowances see Group II)			1					XV601
	M	D			/	/	/				SPACER, SLEEVE: Sig dwg SM-B-143977			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				SPACER, SLEEVE: Sig dwg SM-B-144010			1					
	M	D			/	/	/				SPACER, SLEEVE: Sig dwg SM-B-144307			1					
	M	D			/	/	/				SPRING ASSEMBLY: Sig dwg SM-B-144384			1					
	M	D			/	/	/				SPRING: Sig dwg SM-B-143386			1					
	P1	F		5820-209-9955	/	/	/				SPRING, HELICAL, EXTENSION: Sig dwg SM-B-144257			1	1.0	0.5	2.0		0-608
	P1	F		5820-597-2265	/	/	/				SPRING, HELICAL, EXTENTION: Sig dwg SM-B-144322			1	1.0	0.5	2.0		
	P1	F		5820-696-4921	/	/	/				SPRING, HELICAL, TORSION: Revere Camera #1700-12-2; p/o B-603			1	1.0	0.5	2.0		
	M	D			/	/	/				STRAP ASSEMBLY: Sig dwg SM-C-144380			1					
	M	D			/	/	/				STRAP: Sig dwg SM-B-144006			1					
	M	D			/	/	/				STRAP, LEAD: Sig dwg SM-B-356509			1					
	P1	F		5985-393-2210	/	/	/				STRAP, RETAINING: Sig dwg SM-C-144184			1	1.0	0.5	2.0		
	M	D			/	/	/				STRAP, RETAINING: Sig dwg SM-B-144347			1					
	M	D			/	/	/				STRAP, RETAINING: Sig dwg SM-B-144383			1					
	M	D			/	/	/				STRAP, RETAINING: Sig dwg SM-B-144012			1					
	M	D			/	/	/				STRAP, RETAINING; Sig dwg SM-B-144017			1					
	M	D			/	/	/				STRAP, RETAINING: Sig dwg SM-B-144018			1					
	M	D			/	/	/				SUPPORT ASSEMBLY: Sig dwg SM-C-144246			1					
	M	D			/	/	/				SUPPORT ASSEMBLY: Sig dwg SM-C-144254			1					
	M	D			/	/	/				SUPPORT: Sig dwg SM-C-144022			1					
	M	D			/	/	/				SUPPORT: Sig dwg SM-C-144255			1					
	P1	F		5915-322-4282	/	/	/				SUPPRESSOR, ELECTRICAL NOISE: Sig dwg SM-C-144365			1	1.0	0.5	2.0		
	P1	F		5930-532-7947	/	/	/				SWITCH, ROTARY: Sig dwg SM-B-144195			1	1.0	0.5	5.0		S612

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5930-548-6057	/	/	/				SWITCH, ROTARY: non-pile; Sig dwg SM-A-144316			1	1.0	0.5	5.0		S603
	P1	F		5930-548-6069	/	/	/				SWITCH, ROTARY: Sig dwg SM-A-144313			1	1.0	0.5	5.0		S602
	P1	F		5930-548-8646	/	/	/				SWITCH, ROTARY: Sig dwg SM-A-144315			1	1.0	0.5	5.0		S604
	P1	F		5930-548-9050	/	/	/				SWITCH, ROTARY: Sig dwg SM-A-144314			1	1.0	0.5	5.0		S607
	P1	F		5930-696-5024	/	/	/				SWITCH, ROTARY: Sig dwg SM-A-144320			1	1.0	0.5	5.0		S606
	P1	F		5930-696-5037	/	/	/				SWITCH, ROTARY: Sig dwg SM-A-144317			1	1.0	0.5	5.0		S609
	P1	F		5930-504-8541	/	/	/				SWITCH, SECTION, ROTARY: Sig dwg SM-B-144126			1	1.0	0.5	5.0		S614A
	P1	F		5930-696-5048	/	/	/				SWITCH SECTION, ROTARY: Sig dwg			1	1.0	0.5	5.0		S614B
	P1	F		5930-789-1992	/	/	/				SWITCH SECTION, ROTARY: Collins #269-1585-00; Oak #154407-DAH			1	1.0	0.5	5.0		S605
	P1	F		5930-296-9804	/	/	/				SWITCH, SENSITIVE: spdt; Sig dwg SM-D-143971-22			1	1.0	0.5	5.0		S611
	P1	F		5930-539-7388	/	/	/				SWITCH, SENSITIVE: Electron Switch #S3-4			2	1.0	0.5	10.0		S617
	P1	F		5820-393-1292	/	/	/				SWITCH, SUBASSEMBLY: Collins #5057677002			1	1.0	0.5	5.0		S616
	P1	F		5930-201-5049	/	/	/				SWITCH, THERMOSTATIC: Stevens Mfg #M-82			1	1.0	0.5	5.0		S608
	P1	F		5930-571-1842	/	/	/				SWITCH, THERMOSTATIC: Sig dwg SM-C-144165			1	1.0	0.5	5.0		S610
	M	D			/	/	/				TERMINAL BOARD ASSEMBLY: Sig dwg SM-B-144096			1					
	M	D			/	/	/				TERMINAL BOARD ASSEMBLY: Sig dwg SM-B-144109			1					
	P1	F		5820-865-7271	/	/	/				TERMINAL BOARD ASSEMBLY: Sig dwg SM-B-144111			1	1.0	0.5	2.0		E603
	M	D			/	/	/				TERMINAL BOARD ASSEMBLY: Sig dwg SM-B-144121			1					
	M	D			/	/	/				TERMINAL BOARD ASSEMBLY: Sig dwg SM-B-144251			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	M	D			/	/	/				TERMINAL BOARD ASSEMBLY: Sig dwg SM-B-144252			1					
	M	D			/	/	/				TERMINAL BOARD ASSEMBLY: Sig dwg SM-B-144411			1					
	M	D			/	/	/				TERMINAL BOARD: Sig dwg SM-B-144025			1					
	M	D			/	/	/				TERMINAL BOARD: Sig dwg SM-B-144097			1					
	M	D			/	/	/				TERMINAL BOARD: Sig dwg SM-B-144110			1					
	M	D			/	/	/				TERMINAL BOARD: Sig dwg SM-B-144112			1					
	M	D			/	/	/				TERMINAL BOARD: Sig dwg SM-D-144122			1					
	M	D			/	/	/				TERMINAL BOARD: Sig dwg SM-C-144412			1					
	M	D			/	/	/				TERMINAL ASSEMBLY: Sig dwg SM-B-144416			1					
	M	D			/	/	/				TERMINAL ASSEMBLY: Sig dwg SM-B-144419			1					
	M	D			/	/	/				TERMINAL: Sig dwg SM-B-144381			1					
	M	D			/	/	/				TERMINAL: Sig dwg SM-B-144382			1					
	M	D			/	/	/				CLAMP AND TERMINAL ASSY: Sig dwg SM-B-356812			1					
	M	D			/	/	/				CLAMP AND TERMINAL ASSY: Sig dwg SM-B-356813			1					
	P1	F		5950-757-2081	/	/	/				TRANSFORMER, TORODAL: Sig dwg SM-C-357573			1	1.0	0.5	3.0		T601
	P1	F		5960-013-7338	/	/	/				TRANSISTOR: Clevite #CRT-1500A; Sig dwg SM-D-357530-1			2	*	0.5	6.0		Q601,602
	P1	F		5820-393-1191	/	/	/				TUNER, RF: automatic; Sig dwg SM-C-144031			1	1.0	0.5	3.0		O-644
	P1	F		5820-395-8832	/	/	/				TUNER, RF: automatic; Sig dwg SM-C-144032			1	1.0	0.5	3.0		O-646
		H		5820-396-3057	/	/	/				TUNER, RF: automatic; Sig dwg SM-C-144033			1	1.0	0.5	3.0		O-645
	P1	F		5310-595-5482	/	/	/				WASHER, SPRING TENSION: Sig dwg SM-B-143977			2	1.0	0.5	4.0		

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D										FIGURE NO.	ITEM NO.
						T-195/GRC-19 (continued)								
	M	D			/ / /	WINDOW OBSERVATION: Sig dwg SM-B-144334			1					
	M	D			/ / /	WINDOW, OBSERVATION: Sig dwg SM-B-144335			1					
	M	D			/ / /	WIRING ASSEMBLY, CHASSIS: Sig dwg SM-C-144106			1					
	M	D			/ / /	WIRING ASSEMBLY, PANEL: Sig dwg SM-D-144221			1					
	M	D			/ / /	WIRING ASSEMBLY, SUPPORT: Sig dwg SM-D-144461			1					

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued) GROUP XI POWER SUPPLY, HIGH VOLTAGE, TRANSISTORIZED NOTE: When Power Supply H.V. (5820-682-3393) becomes inoperable or beyond repair it should be replaced by Transistorized Power Supply (5820-962-5383)								
P1 F	5910-682-3760	/	CAPACITOR, FIXED, METALIZED PAPER: 250,000 uuf, ±20%, 400 vdc; Hopkins Eng #P254D			1	1.0	0.5	3.0		C1200
P1 F	5910-713-6862	/	CAPACITOR, FIXED METALIZED PAPER: 1 uuf, ±20%, 600 vdc; Hopkins Eng #P6D			2	1.0	0.5	6.0		C1201, C1202
P1 F	5910-688-7293	/	CAPACITOR, FIXED ELECTROLYTIC: 60 uuf, +20, -15%, 50 vdc; Pyramid Elect #JAK60Mfd			1	1.0	0.5	3.0		C1203
P1 F	5820-542-3328	/	FAN, AXIAL: 4 blades, 55 vac, 1 ph cw rotation; Daven #A-11020-65A			1	1.0	0.3	1.0		B1200
P1 F	5945-752-0246	/	RELAY, ARMATURE: Dpdt, 32 vdc; Daven #11020-63			1	1.0	0.5	3.0		K1200
P1 F	5905-661-0725	/	RESISTOR, FIXED, W/W: 0.1 ohm, ±10%, 5 w; Model Eng #VAL-5 (Item No. R1200 thru R1203, R1209 thru R1212)			8	2.0	1.2	16.0		See Desc column
P1 F	5905-660-9105	/	RESISTOR, FIXED, W/W: 12 ohm, 11 w; MIL #RW29V120			2	1.0	0.5	4.0		R1213, R1214
P1 F	5905-279-4312	/	RESISTOR, FIXED, COMPOSITION: 22 ohm, ±10%, 2 w; MIL #RC42GF220K			1	1.0	0.5	2.0		R1208
P1 F	5905-250-8311	/	RESISTOR, FIXED, COMPOSITION: 470,000 ohm, ±10%, 1 w; MIL #RC32GF474K			2	1.0	0.5	4.0		R1204
P1 F	5960-766-3372	/	SEMICONDUCTOR DEVICE, DIODE: Silicon; Transition Elect #1N604A (Item No. CR1200 thru CR1207, CR1209 thru CR1212)			12	2.0	1.4	24.0		See Desc column
P1 F	5960-583-4704	/	SEMICONDUCTOR DEVICE, DIODE: Transition Elect #1581			1	1.0	0.5	2.0		CR1214

5182-4800

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
P1 F	5950-770-8263	/	TRANSFORMER, POWER ISOLATION AND STEPUP: HS 55 v, sq wave, 1 ph, secd wnd 400 v, 0.5 amp; Daven #B-11020-1			1	1.0	0.5	2.0		T1200
P1 F	5960-828-4242	/	TRANSISTOR: Bendix #2N677B			8	2.0	1.4	16.0		Q1200 thru Q1207
			GROUP XII POWER SUPPLY, HIGH VOLTAGE TRANSISTORIZED								
			NOTE: When Power Supply HV (5820-757-2018) becomes inoperable or beyond repair it should be replaced by Transistorized Power Supply (5820-962-5383)								
P1 F	5910-853-7961	/	CAPACITOR, FIXED: SM-D-357530-2 Sprague #109D306C2100T2 (Authorized allowances based on a total of 3 per equipment.)			2	1.0	0.7	6.0		
P1 F	5910-975-9377	/	CAPACITOR, FIXED PLASTIC: 2 uuf, ±20%, 1200 vdc; Jordan Elect #CX0014			1	1.0	0.5	2.0		C3
P1 F	5910-064-2899	/	CAPACITOR, FIXED PAPER: 8000 uuf, ±5%, 1000 vdc; John E. Fast #278213			2	1.0	0.5	4.0		C1
P1 F	5910-666-4727	/	CAPACITOR, FIXED PAPER DIELECTRIC: 47000 uuf, ±10%, 200 vdc; Sprague #118P4739282			1	1.0	0.5	3.0		C695
P1 F	5910-896-3112	/	CAPACITOR, FIXED, PAPER DIELECTRIC: 200,000 uuf, ±20%, 1500 vdc; Philco #931-0988-00			2	1.0	0.5	6.0		C693, C694
P1 F	5910-847-0883	/	CAPACITOR, FIXED ELECTROLYTIC: 1 uf, 50 vdc; Sprague #40D186A2			2	1.0	0.5	6.0		C689, C690
M D		/	CLAMP, MOUNTING: Sig dwg #SM-B-356748			1					
P1 F	5340-584-1439	/	CLIP, ELECTRICAL: .260 in lg x .625 in w x .325 in h; Sig dwg SM-D-357505-1 (Authorized allowances based on a total of 3.)			2	1.0	0.5	2.0		
P1 F	5340-846-8490	/	CLIP, SPRING TENSION: .333 in lg x 3/4 in w x .377 in h; Awgat #6009-11A			1	0.9	0.3	1.0		

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
										FIGURE NO.	ITEM NO.
A B C D											
			T-195/GRC-19 (continued)								
P1 F	4140-894-0539	/	FAN AXIAL: 2 blades, 2-1/2 in od, 115 v, 1600 cyc, 11700 rpm; Sig dwg SM-D-357503-2			1	1.0	0.5	1.0		
P1 F	5820-757-2019	/	INSULATOR: Sig dwg SM-B-356711 (Authorized allowances based on a total of 10.)			8	2.0	1.4	10.0		
P1 F	5945-808-9755	/	RELAY, ARMATURE: 115 vac, 280 ohm, 28.5 vdc; Sig dwg SM-C-143505			1	1.0	0.5	1.0		K626
P1 F	5905-542-7673	/	RESISTOR, FIXED W/W: 5 ohm; MIL RW59G5RD			8	2.0	1.2	16.0		R699 thru R706
P1 F	5905-823-3385	/	RESISTOR, FIXED W/W: 10 ohm, ±1%, 10 w; Dale #RH-10			2	1.0	0.5	4.0		R697, R698
P1 F	5905-299-2051	/	RESISTOR, FIXED COMPOSITION: 470 ohm, ±5%, 1 w; MIL #RC32GF471J			2	1.0	0.5	4.0		R695, R696
P1 F	5905-845-6247	/	RESISTOR, FIXED W/W: 60,000 ohm, ±3%, 7 w; Sage Elect #SS7W			2	1.0	0.5	4.0		R707, R708
P1 F	5905-299-1994	/	RESISTOR, FIXED COMPOSITION: 470,000 ohm, ±10%, 1 w; MIL RC32GF474K			2	1.0	0.5	4.0		R709, R710
P1 F	5960-845-0766	/	SEMICONDUCTOR DEVICE, DIODE: Motorola #1N2615			10	2.0	1.4	20.0		CR614 thru CR623
P1 F	5960-845-0770	/	SEMICONDUCTOR DEVICE, DIODE: Motorola #1BZ10			1	1.0	0.5	2.0		CR613
P1 F	5950-853-6050	/	TRANSFORMER, POWER, STEP-UP: Hs, pri, 14 v 1600 cyc, 1 ph, 2nd wnds 10 v, ct; Sig dwg SM-D-357526			1	1.0	0.5	1.0		T604
P1 F	5950-895-3463	/	TRANSFORMER, POWER, STEP-UP: Pri, 27.5 v, 1600 cps, 1 ph; Sig dwg SM-D-357524			1	1.0	0.5	1.0		T605
P1 F	5960-806-9655	/	TRANSISTOR: Motorola #2N629 (Authorized allowances based on a total of 10 per equipment.)			8	2.0	1.4	20.0		Q611 thru Q618
P1 F	5960-845-1380	/	TRANSISTOR: Texas Instrument #2N1042-1 (Authorized allowances based on a total of 5.)			2	1.5	0.9	10.0		Q609, Q610

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
										FIGURE NO.	ITEM NO.
A B C D											
			T-195/GRC-19 (continued) GROUP XIII POWER SUPPLY LOW VOLTAGE TRANSISTORIZED NOTE: When Power Supply LV (5820-757-2021) becomes inoperable or beyond repair it should be replaced by Transistorized Power Supply (5820-962-5382)								
P1 F	5910-847-0879		CAPACITOR, FIXED, PLASTIC DIELECTRIC: 10,000 uuf, ±10%, 300 vdc; Sprague #158P10393			2	1.0	0.5	6.0		C680, C687
P1 F	5910-846-6065	/	CAPACITOR, FIXED PAPER DIELECTRIC: 150,000 uuf, ±10%, 200 vdc; Sprague #118P154982			1	1.0	0.5	3.0		C683
P1 F	5910-879-3576	/	CAPACITOR, FIXED: Sig dwg SM-D-357530-3 Sprague #112D307C7030P1			1	1.0	0.5	3.0		C682
P1 F	5910-687-1254	/	CAPACITOR, FIXED, PAPER DIELECTRIC: 2 uf, ±10%, 200 vdc; Sprague #118P205982			1	1.0	0.5	3.0		C681
P1 F	5910-850-3041	/	CAPACITOR, FIXED, ELECTROLYTIC: 4.5 uf, 350 vdc; Sprague #34DS90218			1	1.0	0.5	3.0		C679
P1 F	5910-810-8044	/	CAPACITOR, FIXED ELECTROLYTIC: 4.7 uf, 8 v; Sprague #150D475X9010			2	1.0	0.5	6.0		C684, C688
P1 F	5910-804-8499	/	CAPACITOR, FIXED, ELECTROLYTIC: 4.7 uf, 35 vdc; Sprague #150D475X9035			2	1.0	0.5	6.0		C676, C677
P1 F	5910-846-8382	/	CAPACITOR, FIXED ELECTROLYTIC: 10 uf, 100 vdc; Sprague #40D205A2			2	1.0	0.5	6.0		C685, C686
P1 F	5910-752-4270	/	CAPACITOR, FIXED ELECTROLYTIC: 22 uf, 15 vdc; Sprague #150D226X0015B2			1	1.0	0.5	3.0		C675
P1 F	5910-853-7961	/	CAPACITOR, FIXED, ELECTROLYTIC: 50 uf, 60 vdc; Sprague #109D306C2100T2 (For authorized allowances see Group XII.)			1					C678
P1 F	5340-584-1439	/	CLIP, SPRING TENSION: Atlas #100-200-4-6 (For authorized allowances see Group XII.)			1					

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
										FIGURE NO.	ITEM NO.
A B C D			T-195/GRC-19 (continued)								
P1 F	4140-894-0540	/	FAN, VANE AXIAL: 5 blades; Sig dwg SM-D-357507-1			1	1.0	0.5	2.0		B605
P1 F	5820-757-2019	/	INSULATOR: Sig dwg SM-B-356711 (For authorized allowances see Group XII.)			2					
P1 F	5310-846-7477	/	NUT, PLAIN HEXAGON: 4-40 NC 2 B, 3/16 in across flats x 1/16 in thk; Sig dwg SM-D-357508-26			4	1.0	0.3	4.0		
P1 F	5310-685-4254	/	NUT, PLAIN HEXAGON: Sig dwg SM-D-359509-7			6	1.9	1.0	6.0		
P1 F	5950-845-2723	/	REACTOR: 275 ma dc, 12 ohm; Sig dwg SM-D-357508-1			1	1.0	0.5	2.0		L627
P1 F	5950-845-2724	/	REACTOR: 400 ma dc, 7 ohm; Sig dwg SM-D-357508-2			1	1.0	0.5	2.0		L625
P1 F	5945-847-3915	/	RELAY ARMATURE: Cont arrangement 2 C; Sig dwg SM-D-357508-10			1	1.0	0.5	2.0		K625
P1 F	5905-800-8030	/	RESISTOR, FIXED, W/W: 2.5 ohm, 2.5 w; MIL #RW59G2R5			2	1.0	0.5	6.0		R681, R682
P1 F	5905-583-6172	/	RESISTOR, FIXED, W/W: 40 ohm, ±3%, 15 w; MIL #RH25G40OH			1	1.0	0.5	3.0		R676
P1 F	5905-171-2002	/	RESISTOR, FIXED COMPOSITION: 47 ohm, ±10%, 1/2 w; MIL #RC20GF470K			1	1.0	0.5	3.0		R677
P1 F	5905-845-6248	/	RESISTOR, FIXED W/W: 50 ohm, ±1%, 10 w; Dale Products #RH10			1	1.0	0.5	3.0		R683
P1 F	5905-186-3008	/	RESISTOR, FIXED COMPOSITION: 100 ohm, ±10%, 1/2 w; MIL #RC20GF101K (For authorized allowances see Group VII.)			1					R687
P1 F	5905-171-2005	/	RESISTOR, FIXED COMPOSITION: 470 ohm, ±10%, 1/2 w; MIL #RC20GF471K (For authorized allowances see Group VII.)			1					R694
P1 F	5905-195-6799	/	RESISTOR, FIXED COMPOSITION: 560 ohm, ±10%, 1/2 w; MIL RC20GF561K			3	1.0	0.7	9.0		R679, R680, R692

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
										FIGURE NO.	ITEM NO.
A B C D			T-195/GRC-19 (continued)								
P1 F	5905-279-1722	/	RESISTOR, FIXED COMPOSITION: 1000 ohm, ±10%, 1 w; MIL RC32GF102K (Authorized allowances based on a total of 2.)			1	1.0	0.5	6.0		R686
P1 F	5905-542-9387	/	RESISTOR, FIXED W/W: 1000 ohm, 3 w; MIL #RW59V102			2	1.0	0.5	6.0		R690,R712
P1 F	5905-171-2009	/	RESISTOR, FIXED COMPOSITION: 2200 ohm, ±10%, 1/2 w; MIL RC20GF222K			2	1.0	0.5	6.0		R675,R693
P1 F	5905-845-2745	/	RESISTOR, FIXED W/W: 3500 ohm, ±10%, 10 w; Dale Products #RH10			1	1.0	0.5	3.0		R688
P1 F	5905-299-2039	/	RESISTOR, FIXED COMPOSITION: 3900 ohm, ±10%, 1 w; MIL RC32GF392K			1	1.0	0.5	3.0		R691
P1 F	5905-845-2741	/	RESISTOR, FIXED W/W: 10,000 ohm, ±1%, 10 w; Dale Products #RH10			1	1.0	0.5	3.0		R685
P1 F	5905-279-2655	/	RESISTOR, FIXED COMPOSITION: 56,000 ohm, ±10%, 2 w; MIL RC42GF563K			1	1.0	0.5	3.0		R684
P1 F	5905-254-7090	/	RESISTOR, FIXED COMPOSITION: 68,000 ohm, ±10%, 2 w; MIL RC42GF683K			1	1.0	0.5	3.0		R711
P1 F	5905-846-8004	/	RESISTOR, VARIABLE: 10 ohm, ±10%, 12.5 w; Philco #363-5119-1			1	1.0	0.5	3.0		R678
P1 F	5950-847-3917	/	SATURABLE REACTOR: 120 v min -160 v max 400 cyc, 1 ph; Philco #362-1416-1			1	1.0	0.5	3.0		L626
P1 F	5960-845-0762	/	SEMICONDUCTOR DEVICE, DIODE: Motorola #2N2613 (Item No. CR604 thru CR607, CR609 thru CR612)			8	2.0	1.2	24.0		See Desc column
P1 F	5960-556-2091	/	SEMICONDUCTOR DEVICE, DIODE: MIL 1N270			1	1.0	0.5	3.0		CR608
P1 F	5960-850-6716	/	SEMICONDUCTOR DEVICE, DIODE: Motorola #3/4M.7.525			1	1.0	0.5	3.0		CR603
P1 F	5950-859-2599	/	TRANSFORMER, AUDIO FREQUENCY: Sig dwg SM-D-357525			1	1.0	0.5	3.0		T603

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5950-859-2598			/				TRANSFORMER, AUDIO FREQUENCY: Sig dwg SM-D-357225			1	1.0	0.5	3.0		T602
	P1	F		5960-845-1377			/				TRANSISTOR: Sylvania #2N385A			1	1.0	0.5	3.0		Q608
	P1	F		5960-806-9655			/				TRANSISTOR: Motorola #2N629 (For authorized allowances see Group XII.)			2					Q606, Q607
	P1	F		5960-845-1380			/				TRANSISTOR: Texas Instrument #2N1042-1 (For authorized allowances see Group XII.)			3					Q603, Q604, Q605
											GROUP XIV TRANSMITTER, DISCRIMINATOR SUBASSEMBLY								
	P	H	R	5820-096-6989	/	/	/				TRANSMITTER, SUBASSEMBLY: Sig dwg SM-C-143925		NX	1		0.5	2.0		
	M	D			/	/	/				ARM: 1-23/64 in lg x 1/4 in w x .032 in h; Sig dwg SM-C-143934 (p/o contact assy P303)			1					
	M	D			/	/	/				BRACKET ASSY: Sig dwg SM-B-143930			1					
	M	D					/				BRACKET: Sig dwg SM-B-143935			1					
	P1	F		5910-112-7910	/	/	/				CAPACITOR, FIXED, CERAMIC DIELECTRIC: 30 uuf, ±5%, 500 vdc; MIL #CC30CH300J			1	1.0	0.5	3.0		C306
	P1	F		5910-667-6198	/	/	/				CAPACITOR, FIXED CERAMIC DIELECTRIC: 43 uuf, ±5%, 500 vdc; MIL #CC30CH430J			1	1.0	0.5	3.0		C307
	P1	F		5910-248-2212	/	/	/				CAPACITOR, FIXED CERAMIC DIELECTRIC: 75 uuf ±2% 500 vdc; MIL CC30UJ750G			1	1.0	0.5	3.0		C308
	P1	F		5910-667-5730	/	/	/				CAPACITOR, FIXED CERAMIC DIELECTRIC: 1000 uuf, ±10%, 500 vdc; Erie #370			1	1.0	0.5	3.0		C302
	P1	F		5910-265-3295	/	/	/				CAPACITOR, FIXED PAPER DIELECTRIC: 10,000 uuf, ±10%, 300 vdc; Sprague #75P10392 (For authorized allowances see Group III.)			2					C303
	P1	F		5910-197-6715	/	/	/				CAPACITOR, VARIABLE: 3 to 12 uuf, 350 vdc; Sig dwg SM-B-91276 (For authorized allowances see Group VIII.)			1					C505

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL							DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D																FIGURE NO.	ITEM NO.
												T-195/GRC-19 (continued)								
	M	D			/	/	/					CHANNEL ASSEMBLY: Sig dwg SM-B-143938			1					
	M	D			/	/	/					CHASSIS ASSEMBLY: Sig dwg SM-B-143953			1					
	M	D			/	/	/					CLAMP, RETAINING: Sig dwg SM-D-143926			1					C502
	P1	F		5935-636-5913	/	/	/					CONNECTOR, RECEPTACLE, ELECTRICAL: 7 rd male cont; Sig dwg SM-C-283198 (For authorized allowances see Group IX.)			1					P302
	P1	F		5820-502-6108	/	/	/					CONTACT, ELECTRICAL: 1 brass point; Sig dwg SM-B-143933			1	1.0	0.5	2.0		P303
	P1	F		5820-502-6109	/	/	/					CONTACT, ELECTRICAL: 2 brass points; Sig dwg SM-B-143965			2	1.0	0.5	4.0		P301,P304
	P1	F		5935-521-0574	/	/	/					COVER, CONNECTOR: P/o P302; Sig dwg SM-B-283197 (For authorized allowances see Group IX.)			1					
	M	D			/	/	/					COVER: Sig dwg SM-C-143928			1					
	M	D			/	/	/					PLATE: Sig dwg SM-C-143936			1					
	P1	F		5905-256-0411	/	/	/					RESISTOR, FIXED COMPOSITION: 180 ohm, ±10%, 1 w; MIL RC32GF181K			1	1.0	0.5	3.0		R303
	P1	F		5905-107-4126	/	/	/					RESISTOR, FIXED COMPOSITION: 820 ohm, ±10%, 1 w; MIL RC32GF821K			1	1.0	0.5	3.0		R308
	P1	F		5905-279-1722	/	/	/					RESISTOR, FIXED COMPOSITION: 1000 ohm, ±10% 1 w; MIL RC32GF102K (For authorized allowances see Group XIII.)			1					R310
	P1	F		5905-279-2672	/	/	/					RESISTOR, FIXED COMPOSITION: 1800 ohm, ±10%, 1/2 w; MIL RC20GF182K (For authorized allowances see Group II.)			1					R309
	P1	F		5905-171-2004	/	/	/					RESISTOR, FIXED, COMPOSITION: 22,000 ohm, ±5%, 1/2 w; MIL RC20GF223J			4	1.5	0.8	12.0		R301, R302, R304
	P1	F		5905-195-6758	/	/	/					RESISTOR, FIXED COMPOSITION: 27,000 ohm ±10% 1/2 w; MIL RC20GF273K (For authorized allowances see Group II.)			2					R306,R307

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL							DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D																FIGURE NO.	ITEM NO.
												T-195/GRC-19 (continued)								
	P1	F		5960-780-2609	/	/	/					SEMICONDUCTOR DEVICE SET: Matched Pair 1N67A, Hughes Aircraft #MP3602A (For authorized allowances see Group III.)			1					CR301, CR302
	P1	F		5960-284-6516	/	/	/					SEMICONDUCTOR DEVICE DIODE: MIL 1N198			2	1.0	0.5	6.0		CR303, CR304
	M	D			/	/	/					SHIM: Sig dwg SM-B-143937			1					
	M	D			/	/	/					TERMINAL BOARD: Sig dwg SM-C-143941			1					
	M	D			/	/	/					TERMINAL BOARD SUBASSY: Sig dwg SM-C-143948			1					
	M	D			/	/	/					TERMINAL BOARD: Sig dwg SM-B-143927			1					
	P1	F		5950-523-8418	/	/	/					TRANSFORMER, DISCRIMINATOR: 400 cps, peak freq, unshielded; Sig dwg SM-C-143958			1	1.0	0.5	2.0		L304
	M	D			/	/	/					WIRING ASSEMBLY: Sig dwg SM-B-143956			1					
												GROUP XV TUNER, R. F. INDUCTOR SUBASSEMBLY								
	P1	H	R	5820-539-6348	/	/	/					TUNER, R. F. VARIABLE: (Inductor sub-assembly) freq 0.5 to 32 mc, 1 term 20 pin connector; Sig dwg SM-B-143805		NX	1		0.5	3.0		
	M	D			/	/	/					BLOCK: Sig dwg SM-B-143820			1					
	M	D			/	/	/					BLOCK: Sig dwg SM-B-143849			2					
	M	D			/	/	/					BRACKET: Sig dwg SM-B-143807			1					
	M	D			/	/	/					BRACKET: Sig dwg SM-B-143814			1					
	M	D			/	/	/					BRACKET: Sig dwg SM-B-143910			1					
	P1	F		5820-696-4724	/	/	/					BUSHING, COIL ADJUSTMENT: Comp plastic, lam nylon, fabric base rod, rd shape; Sig dwg SM-B-143808			1	1.0	0.5	2.0		01113
	M	D			/	/	/					CABLE ASSEMBLY: Sig dwg SM-D-143841			1					

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		5910-667-5247	/	/	/				CAPACITOR, FIXED PAPER DIELECTRIC: 270,000 uuf, ±10%, 120 vdc; Sprague #P71131			1	1.0	0.5	3.0		C1101
	M	D			/	/	/				CLAMP, LOOP: Sig dwg SM-B-143813			1					
	P1	F		5975-396-3116	/	/	/				CLAMP, LOOP: Sig dwg SM-B-144451 (For authorized allowances see Group IV.)			1					H1106
	P1	F		5935-173-5908	/	/	/				CONNECTOR, RECEPTACLE, ELECTRICAL: 20 rd male cont; Sig dwg SM-B-283188 (For authorized allowances see Group VII.)			1					P1101
	P1	F		5950-500-6272	/	/	/				CONTACT, ELECTRICAL: (Arm assy); Sig dwg SM-B-143824			2	1.0	0.5	4.0		J1101, J1102
	P1	F		5820-696-4756	/	/	/				DRUM, PINNED: Cont, brass; Sig dwg SM-B-143856			1	1.0	0.5	2.0		E1105
	P1	F		5950-648-1478	/	/	/				FORM, COIL: Ceramic (for L1101); Sig dwg SM-D-143835			1	1.0	0.5	2.0		
	P1	F		5820-696-4723	/	/	/				GEAR, ASSEMBLY: Sig dwg SM-B-143861			1	1.0	0.5	2.0		01102
	P1	F		5820-696-4726	/	/	/				GEAR, ASSEMBLY: Sig dwg SM-B-143874			1	1.0	0.5	2.0		01101
	P1	F		5820-696-4758	/	/	/				GEAR, ASSEMBLY: Sig dwg SM-B-143861			1	1.0	0.5	2.0		01104
	P1	F		5820-696-4759	/	/	/				GEAR, ASSEMBLY: Sig dwg SM-C-143881			1	1.0	0.5	2.0		01109
	P1	F		5820-561-0944	/	/	/				GEAR, SPUR: Sig dwg SM-C-143885			1	1.1	0.5	2.0		01103
	P1	F		5820-561-0945	/	/	/				GEAR, SPUR: Sig dwg SM-C-143834			1	1.0	0.5	2.0		01110
	P1	F		5820-696-4725	/	/	/				GEAR SPUR: Sig dwg SM-B-143817			1	1.0	0.5	2.0		01108
	P1	F		5820-696-4740	/	/	/				GEAR, SPUR: Sig dwg SM-B-143877			1	1.0	0.5	2.0		01107
	P1	F		5820-696-4760	/	/	/				LEVER, TRIP: Sig dwg SM-B-143855			1	1.0	0.5	2.0		01112
	P1	F		6615-322-5365	/	/	/				MOTOR, CONTROL: 400 cyc, 115 v, 0.260 amp, 1030 ohm; Kearfoot type T-110-2B-C (For authorized allowances see Group III.)			1					B1101

SOURCE CODE				FEDERAL STOCK NUMBER	DESIGNATION BY MODEL						DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A	B	C	D															FIGURE NO.	ITEM NO.
											T-195/GRC-19 (continued)								
	P1	F		6105-696-5606	/	/	/				MOTOR, D. C.: 27.5 v, 0.4 amp, 8,200 rpm: Sig dwg SM-C-143844			1	1.0	0.5	2.0		B1102
	M	D			/	/	/				PLATE ASSEMBLY: Sig dwg SM-C-143819			1					
	M	D			/	/	/				PLATE ASSEMBLY: Sig dwg SM-B-143821			1					
	M	D			/	/	/				PLATE ASSEMBLY: Sig dwg SM-B-143826			1					
	M	D			/	/	/				PLATE ASSEMBLY: Sig dwg SM-C-143843			1					
	M	D			/	/	/				PLATE ASSEMBLY: Sig dwg SM-B-143864			1					
	M	D			/	/	/				PLATE ASSEMBLY: Sig dwg SM-B-143899			1					
	M	D			/	/	/				PLATE: Sig dwg SM-B-143810			1					
	M	D			/	/	/				PLATE: Sig dwg SM-B-143851			1					
	M	D			/	/	/				PLATE: Sig dwg SM-C-143823			1					
	M	D			/	/	/				POST, BINDING: Sig dwg SM-B-143310			5					
	M	D			/	/	/				POST, BINDING: Sig dwg SM-B-143806			2					
	M	D			/	/	/				POST BINDING: Sig dwg SM-B-143812			2					
	P1	F		5905-100-4002	/	/	/				RESISTOR, FIXED W/W: 5 ohm, ±5%, 8 w; MIL #RW30G5R0 (For authorized allowances see Group X.)			1					R1101
	P1	F		5340-282-0782	/	/	/				RING, RETAINING: Waldes Pt #5100-25-C			1	1.0	0.5	2.0		H1104
	P1	F		5340-282-0813	/	/	/				RING, RETAINING: Waldes #5133-18-S (For authorized allowances see Group III.)			14					
	P1	F		5340-282-7102	/	/	/				RING, RETAINING: Waldes #5100-50-C			2	1.0	0.5	4.0		
	P1	F		5340-598-1229	/	/	/				RING, RETAINING: Waldes #5133-6			1	1.0	0.5	2.0		H1105
	P1	F		5340-619-3376	/	/	/				RING, RETAINING: Waldes #5133-12-S (For authorized allowances see Group VIII.)			5					

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
P1 F	5305-754-3173	/ / /	SCREW, CAP, SOCKET HEAD: 4-40 NC 2A, 1/2 in lg			8					
M D		/ / /	SHAFT ASSY: Sig dwg SM-B-143836			1					
P1 F	5930-696-4920	/ / /	SHAFT, SWITCH: Sig dwg SM-B-143854			1	1.0	0.5	2.0		01111
M D		/ / /	SHAFT: Sig dwg SM-B-143889			1					
M D		/ / /	SPACER, SLEEVE: Sig dwg SM-B-143850			2					
M D		/ / /	SPACER, SLEEVE: Sig dwg SM-B-143852			2					
M D		/ / /	SPACER, SLEEVE: Sig dwg SM-B-143853			1					
P1 F	5820-598-4937	/ / /	SPRING, HELICAL, EXTENSION: Sig dwg SM-B-143848			2	1.0	0.5	4.0		01105
P1 F	5820-721-8948	/ / /	SPRING, HELICAL, EXTENSION: Sig dwg SM-B-143882			2	1.0	0.5	4.0		
P1 F	5930-548-6953	/ / /	SWITCH, ROTARY: Sig dwg SM-B-143847			1	1.0	0.5	3.0		S1101A
P1 F	5930-636-2605	/ / /	SWITCH, ROTARY: Sig dwg SM-B-143846			1	1.0	0.5	3.0		S1101B
P1 F	5950-571-2564	/ / /	TUBE-CORE, COIL CEMENTED: Sig dwg SM-B-143920			1	1.0	0.5	2.0		
M D		/ / /	WASHER: Sig dwg SM-B-143883			9					
M D		/ / /	WASHER, SPRING TENSION: Sig dwg SM-B-178766			1					
M D		/ / /	WASHER, KEY WAY: Sig dwg SM-B-143888			2					
			GROUP XVI POWER SUPPLY TRANSISTORIZED, HIGH VOLTAGE								
P1 H R	5820-962-5383	/	POWER SUPPLY, TRANSISTORIZED, HIGH VOLTAGE: Sig dwg SM-D-283619			1	1.0	0.5	3.0		
P1 F	5910-975-9377	/	CAPACITOR, FIXED, PLASTIC DIELECTRIC: 2 uf, ±20%, 1200 vdc; Jordan Elect #CX-0014			1	1.0	0.5	3.0		C1

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
										FIGURE NO.	ITEM NO.
A B C D			T-195/GRC-19 (continued)								
P1 F	5910-064-2899	/	CAPACITOR, FIXED, PLASTIC DIELECTRIC: 8000 uuf, ±5%, 1000 vdc; John E. Fast #278213			2	1.0	0.5	6.0		C3
P1 F	5820-974-7685	/	CONTROL MODULE: 118 v, 1.5 kc freq; Jordan Elect #AE-0264			1	1.0	0.5	2.0		Z2
P1 F	5820-063-9034	/	FAN, AXIAL: 8 blades, 165 v 1 ph, 1500 rpm; Jordan Elect #AE0255			1	1.0	0.5	2.0		Z4
P1 F	5960-974-9812	/	HEAT SINK, SEMICONDUCTOR: Jordan Elect #MM-0494			2	1.0	0.5	4.0		
P1 F	5820-974-7684	/	POWER SUPPLY SUBASSEMBLY, MODULE: 0.5 amp 1000 vdc; Jordan Elect #AE-0270			1	1.0	0.4	2.0		Z3
P1 F	5905-191-5000	/	RESISTOR, FIXED W/W: 2 ohm ±5%, 10 w; MIL #RW312RO			2	1.0	0.5	6.0		R1,R2
P1 F	5960-581-8274	/	SEMICONDUCTOR DEVICE DIODE: MIL #1N-253			2	1.0	0.6	6.0		CR1,CR2
P1 F	5960-577-6084	/	SEMICONDUCTOR DEVICE DIODE: MIL #1N-645			2	1.0	0.6	6.0		
P1 F	5820-974-7683	/	START MODULE: Input voltage 28.5 vdc, output 1 ph; Jordan Elect #AE-0258; (Authorized allowances based on a total of 2.)			1	1.0	0.5	4.0		Z1
P1 F	5950-975-7099	/	TRANSFORMER POWER: 1 ph, 500 cy; Jordan Elect #TC-0003			1	1.0	0.5	3.0		T1
P1 F	5960-889-3968	/	TRANSISTOR: Bendix Corp #2N1652			2	1.0	0.5	6.0		Q1,Q2
P1 F	5330-889-2581	/	WASHER, SHOULDERED: Fiber; H. H. Smith #2156			4	1.0	0.6	4.0		
			GROUP XVII POWER SUPPLY, TRANSISTORIZED LOW VOLTAGE								
P1 H R	5820-962-5382	/	POWER SUPPLY, LOW VOLTAGE: Sig dwg SM-D-283618			1		0.5	3.0		
P1 F	5820-063-9035	/	FAN, AXIAL: 8 blades, 125 v 1 ph, 10,500 rpm; Jordan Elect #AE-0223			1	1.0	0.4	2.0		Z4

SOURCE CODE	FEDERAL STOCK NUMBER	DESIGNATION BY MODEL	DESCRIPTION	UNIT OF ISSUE	EXP	QTY IN UNIT	DIRECT SUPPORT	GENERAL SUPPORT	DEPOT	ILLUSTRATION	
A B C D										FIGURE NO.	ITEM NO.
			T-195/GRC-19 (continued)								
P1 F	5820-974-7688	/	FREQUENCY CONTROL MODULE: Input voltage 25.5 vdc, output 1.25 millisecond; Jordan Elect #AE-0257			1	1.0	0.5	2.0		Z2
P1 F	5960-974-9811	/	HEAT SINK, SEMICONDUCTOR DEVICE: Jordan Elect #MM-0477			2	1.0	0.5	2.0		
P1 F	5820-974-7687	/	POWER SUPPLY SUBASSEMBLY MODULE: 45 vdc, 0.010 amp; Jordan Elect #AE-0274			1	1.0	0.5	2.0		Z5
P1 F	5820-974-7686	/	POWER SUPPLY SUBASSEMBLY MODULE: 250 vdc, 0.3 amp; Jordan Elect #AE-0273			1	1.0	0.5	2.0		Z6
P1 F	5820-974-7683	/	START MODULE: Input voltage 28.5 vdc, output 1 ph; Jordan Elect #AE-0258 (For authorized allowances see Group XVI.)			1					Z1
P1 F	5820-974-7689	/	TRANSMITTER INDUCTOR MODULE: Pri wnd 5 v at 1 amp, 27.5 v at 400 cps, sec wnd 115 v at 30 amp, 45 v at 0.010 amp, 250 v at 0.3 amp, inductor hy 0.140 hy, 0.210 hy; Jordan Elect #AE-0221			1	1.0	0.5	2.0		
P1 F	5960-974-9806	/	TRANSISTOR ASSEMBLY: Jordan Elect #AE-0229			2	1.0	0.5	4.0		
P1 F	5960-088-2783	/	TRANSISTOR: Motorola #2N1532			2	1.0	0.5	4.0		Q1,Q2

By Order of the Secretary of the Army:

HAROLD K. JOHNSON,
General, United States Army,
Chief of Staff.

Official:

J. C. LAMBERT,
Major General, United States Army,
The Adjutant General.

Distribution:

Active Army:

USASA (2)
CNGB (1)
CC–E (7)
Dir of Trans (1)
CofEngrs (1)
TSG (1)
CofSptS (1)
USACDCEA (1)
USACDCCBRA (1)
USACDCEA (1)
USACDCOA (1)
USACDCQMA (1)
USACDCTA (1)
USACDCADA (1)
USACDCARMA (1)
USACDCAVNA (1)
USACDCARTYA (1)
USACDCSWA (1)
USACDCCEA, Ft Huachuca (1)
USACDCEC (10)
USATCFE (5)
USAMC (5)
USCONARC (5)
ARADCOM (5)
ARADCOM Rgn (2)
OS Maj Comd (4)
LOGCOMD (2)
USAMICOM (4)
USASMC (2)
USASCC (4)
MDW (1)
Armies (2) except
EUSA (5)
Corps (2)
USAC (3)
11th Air Aslt Div (3)
1st GM Bde (5)
318th USASA Bn (5)
319th USASA Bn (5)
400th USASA Det (5)
401st USASA Det (5)
402d USASA Det (5)
403d USASA Det (5)
1st USASA Fld Sta (5)
4th USASA Fld Sta (5)
USATC (2)
Svc Colleges (2)
Br Svc Sch (2) except
USASESCS (60)
USAES (5)
USAAMS (5)
MFSS (5)
USASCS (5)
USAARMS (5)
USAADS (5)
USMA (5)
MGH (5)
WRAMC (1)
Instl (2) except
Ft Monmouth (70)
Ft Gordon (10)
Ft Huachuca (10)
Ft Carson (21)
Ft Knox (12)
Ft Devens (5)
Ft Belvoir (5)
WSMR (5)
Army Pic Cen (2)
USAINTC (5)
Army Dep (2) except
LBAD (14)
SAAD (30)
TOAD (14)
FTWOAD (10)
LEAD (7)
SHAD (3)
NAAD (5)
SVAD (5)
CHAD (3)
ATAD (10)
UTAD (5)
Gen Dep (2)
Sig Sec, Gen Dep (5)
Sig Dep (12)
Sig Fld Maint Shops (2)
AMS (1)
USAERDAA (2)
USARDAW (13)
USCRREL (2)
KMAG (5)
USARMIS, Ecuador (5)
Units org under fol TOE (2 cys ea):
11–57
11–97
11–98
11–117
11–127
11–155
11–157
11–500 (Tms AA–AC)
11–587
11–592
11–597

NG: State AG (3); Units — Same as Active Army except allowance is one copy to each unit.

USAR: None.

For explanation of abbreviations used see AR 320–50.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1966—204431/1640